


International ICR Rectifier

153CMQ... SERIES

SCHOTTKY RECTIFIER

150 Amp




Major Ratings and Characteristics

Characteristics	153CMQ...	Units
I _{F(AV)} Rectangular waveform	150	A
V _{RRM} range	80 to 100	V
I _{FSM} @ tp = 5 µs sine	7000	A
V _F @ 75Apk, T _J = 125°C (per leg)	0.80	V
T _J range	-55 to 175	°C

Description/ Features

The 153CMQ isolated center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175°C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 175°C T_J operation
- Isolated heatsink
- Center tap module
- Multiple leads per terminal for high frequency, high current PC board mounting
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Low profile, high current package



Voltage Ratings

Part number	153CMQ080	153CMQ090	153CMQ100
V_R Max. DC Reverse Voltage (V)	80	90	100
V_{RWM} Max. Working Peak Reverse Voltage (V)			

Absolute Maximum Ratings

Parameters	153CMQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	150	A	50% duty cycle @ $T_C = 90^\circ\text{C}$, rectangular wave form
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	7000	A	5μs Sine or 3μs Rect. pulse
	720		Following any rated load condition and with 10ms Sine or 6ms Rect. pulse rated V_{RRM} applied
E_{AS} Non-Repetitive Avalanche Energy (Per Leg)	15	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 1$ Amps, $L = 30$ mH
I_{AR} Repetitive Avalanche Current (Per Leg)	1	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	153CMQ	Units	Conditions		
V_{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.96	V	@ 75A	$T_J = 25^\circ\text{C}$	
	1.19	V	@ 150A		
	0.80	V	@ 75A	$T_J = 125^\circ\text{C}$	
	0.99	V	@ 150A		
I_{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	1.5	mA	$T_J = 25^\circ\text{C}$	$V_R = \text{rated } V_R$	
	20	mA	$T_J = 125^\circ\text{C}$		
C_T Max. Junction Capacitance (Per Leg)	1400	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C		
L_S Typical Series Inductance (Per Leg)	9.2	nH	Measured lead to lead 5mm from package body		
dv/dt Max. Voltage Rate of Change (Rated V_R)	10000	V/ μs			

(1) Pulse Width < 300μs, Duty Cycle <2%

Thermal-Mechanical Specifications

Parameters	153CMQ	Units	Conditions	
T_J Max. Junction Temperature Range	-55 to 175	°C		
T_{stg} Max. Storage Temperature Range	-55 to 175	°C		
R_{thJC} Max. Thermal Resistance Junction to Case (Per Leg)	1.0	°C/W	DC operation	* See Fig. 4
R_{thJC} Max. Thermal Resistance Junction to Case (Per Package)	0.50	°C/W	DC operation	
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.10	°C/W	Mounting surface, smooth and greased	
wt Approximate Weight	56(2.0)	g(oz.)		
T Mounting Torque	Min.	40(35)	Kg-cm	
	Max.	58(50)	(lbf-in)	
Case Style	D-60(TO-249AA)		Modified JEDEC	




Fig. 1 - Max. Forward Voltage Drop Characteristics
 (Per Leg)




Fig. 2 - Typical Values Of Reverse Current
 Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance
 Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)




Fig. 5-Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6-Forward Power Loss Characteristics (Per Leg)




Fig. 7-Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8-Unclamped Inductive Test Circuit

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 05/02