

American Hakko Products, Inc.



Bulletin No: PB336

Issue Date: 5-6-2013

Available: 5-10-2013

Product Description:

Odor Filter for the Hakko FA-430

Part No:

999-245

Specification:

opecification		
Dimensions	Unit	270 x 220 x 125mm
$(L \times W \times H)$		(10.6 x 8.6 x 5 in.)
	Shipping	292 x 229 x 165 mm
		(11.5 x 9 x 6.5 in.)
Weight	Unit	1679 g (3.7 lb.)
	Shipping	1951 g (4.3 lb.)
Filtering Efficiency		>98% of particulate to 0.3μ m
Media Type		Activated Carbon
Media Area		1.239 m ² (13.34 ft ²)
Activated Carbon		600g
Content		-
Carbon Activity Level		1100 mg/g minimum
Carbon Chloride No.		60%
Adsorption Capacity		Approx. 360g ¹

1 – Adsorption Capacity based on ASTM D3467 for Carbon Tetrachloride Activity of Activated Carbon

Comment:

The Hakko 999-245 Carbon Odor Filter is designed as an optional filter that can be used in the Hakko FA-430 Fume Extraction System when the primary use of the system is to remove odors created by various processes. The pleated media contains highly activated carbon and provides a greater gas adsorption area compared to the activated carbon portion of the standard main filter that comes with the Hakko FA-430 Fume Extraction System.

NOTE: This filter will also trap particulates therefore the use of the Hakko A1585 Pre-Filter is required to ensure maximum filter life.

For more information, visit us online at www.HakkoUSA.com or call us at 1-800-88-HAKKO (42556).