


596-00654

HellermannTyton

Article Number: 596-00654



Description: Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll

Base Data	Local Order Number	596-00654
	Type	DCRATING-1
	Color	Red (RD)
	Features and benefits	<ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Printable Solar Label, DC RATING LABEL, 2.0" X 3.75", Red
	Short Description	Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll
Product Dimensions	Width W (Imperial)	3.75"
	Width W (Metric)	92.25mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
	Material and Specifications	Material
Material Shortcut		PET
Adhesive		Acrylic
Adhesive Operating Temperature		-40°F to +180°F (-40°C to +82°C)

596-00654



Material and Specifications	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055