Samsung ARTIK™



PRODUCT BRIEF



Samsung's ARTIK™ 520 Module is a highly-integrated System-in-Module that utilizes a dual core ARM® Cortex®-A7 processor packaged DRAM and Flash memories, a Secure Element and a wide of wireless communication options such range as 802.11a/b/g/n/ac, Bluetooth® 4.1, Bluetooth Low Energy (BLE), and 802.15.4/ZigBee® communications all into a 30x25mm footprint. The many standard digital control interfaces support external sensors and higher performance peripherals to expand the module capabilities. With the combination of Wi-Fi, Bluetooth and ZigBee, the ARTIK 520 Module is the perfect choice for home automation and home hub devices, while also supporting a rich UI/UX capability with the camera and display options. The hardware based Secure Element works with the ARM® TrustZone® and Trustonic's Trusted Execution Environment (TEE) to provide "bank level" security end-to-end.

TOP VIEW

BOTTOM VIEW



ARTIK 520 Module Block Diagram

Processor	
CPU	Dual core ARM® Cortex®-
CPU	A7@1.0GHz
GPU	Mali™-400MP2 core
Media	
	1x 2-Lane MIPI CSI up to
Camera I/F	3MP@30fps (Supports YUV
	and MJPEG format)
Display	2-Lane MIPI DSI up to qHD
Display	960x540@24bpp
A	1-channel PCM and 1-channel
Audio	24-bit I2S audio interface
Memory	
DRAM	512MB LPDDR3
FLASH	4GB eMMC
Security	
	Secure point to point
Secure Element	authentication and data
	transfer
Trusted Execution Environment	Trustonic TEE (NDA required)
Radio	
WLAN	IEEE 802.11a/b/g/n/ac
Bluetooth	BT/BLE
IEEE802.15.4	ZigBee
Power Management	
	Provides all power of the ARTIK
PMIC	520 Module using on board
	bucks and LDO's
Interfaces	
Analog and Digital I/O	GPIO, I ² C, SPI, UART, SDIO,
	USB 2.0, JTAG, Analog Input

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppel or other-wise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office. All brand names, trademarks and registered trademarks belong to their respective owners.





ARTIK 520 Module Processor Sub System

APP FRAMEWORK AP

SUSPEND TO RAM

CPU IDLE

DEV FREQUENCY

MANAGER

ARTIK 520 MODULE

ARTIK 520 Module Software Stack

LCD

SD MMC

PWM

ZIGBEE

ADC

SDIO

GPIO

PMIC

Processors	Dual core ARM® Cortex® A7@1.0GHz 32KB I\$ and 32KB D\$ per core Shared 1MB L2 Cache
Display/Camera	Camera I/F 3MP@30fps 1-channel, 2-lane MIPI CSI@1Gbps D- PHY (Supports YUV and MJPEG format) 1-channel, 2-lane MIPI DSI@qHD
DMC	Support for SRAM/NOR/ROM LPDDR2 interface@533MHz LPDDR3 interface@667MHz
External Peripherals	2xSPI, 2xUART (4-pin), 1xUART (2-pin) 6xI2C+1xI2C (Camera), 1xI2S/PCM 2-channel ADC 100xGPIO (multiplexed)
Multi Media	Mali™-400 graphics accelerator JPEG Codec
High Speed Interfaces	1xUSB2.0 1-channel SD/SDIO eMMC5.0
Security	Secure Hash

ARTIK 520 MODULE SECURITY FEATURES

Samsung considers world class security as one of the most important requirements when adding IoT nodes into the cloud. As such Samsung build its IoT ARTIK product family with a security architecture in mind. To assure a secure environment for all IoT nodes, the ARTIK family has dedicated security hardware and software components in place.

Every ARTIK 520 Module has the ability to authenticate its boot image using a secure hash and execute a secure boot once the boot image has been authenticated. Secure communication and key management is facilitated by the Secure Element as part of any ARTIK 520 Module. Finally secure execution can be performed in Trustonic's Trusted Execution Environment (TEE) using ARM® TrustZone®.

The ARTIK 520 Module software stack as described facilitates total security starting from authenticated adoption of an ARTIK 520 Module IoT node into the cloud to secure communication and remote software updates.

Samsung's commitment to security gives developers the ability to create secure user experiences using the ARTIK 520 Module.

APP-N

MOTT

LW M2M

TZ MONITOR

CRYPTO LIBRARY

SECURITY S-SAFE

TEE CRY

IoT SECURITY/SECURE PAIRING/DOMAIN MANAGEMENT

SELINUX

SECURE BOOT

NETWORK PROTOCOLS

TLS/DTLS SSL

TZW

TOSS

COAP

IPv6

NAGER

RUNTIME PM

ASV

CLOCK MANAGEI

CPU FREQUENC

ARTIK 520 MODULE ORDERING INFORMATION

For volume ordering of the evaluation kits, please contact a sales representative in your area or email sales@artik.io.



APP-1

CAMERA

UART

CAMERA HA

BT BLE

U-8001

RTC

SYSTEM TIMER

I²C

APP-2

BSP STACK

USB

Wi-Fi

INT

DMA

WATCH DOG

тоисн

MULTI MEDU

AUDIO