



SIPMOS® Small-Signal-Transistor
Product Summary
Feature

- n-channel
- enhancement mode
- Logic level
- dv/dt rated
- Qualified according to AEC Q101

V_{DS} ¹⁾	600	V
$R_{DS(on),max}$	45	Ω
I_D	0.09	A



SOT89



Type	Package	Pb-free	Tape and Reel Information	Marking
BSS225	SOT89	Yes	L6327: 3000PCS/reel	KD

Maximum ratings, at $T_j=25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	$T_A=25^\circ\text{C}$	0.09	A
		$T_A=70^\circ\text{C}$	0.073	
Pulsed drain current	$I_{D,pulse}$	$T_A=25^\circ\text{C}$	0.36	
Reverse diode dv/dt	dv/dt	$I_D=0.09 \text{ A}$, $V_{DS}=480 \text{ V}$, $di/dt=200 \text{ A}/\mu\text{s}$, $T_{j,max}=150^\circ\text{C}$	6	kV/ μs
Gate source voltage	V_{GS}		± 20	V
ESD Class JESD22-A114-HBM			Class 1a	
Power dissipation	P_{tot}	$T_A=25^\circ\text{C}$	1.00	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Thermal characteristics

Thermal resistance, junction - minimal footprint	R_{thJA}		-	-	125	K/W
---	-------------------	--	---	---	-----	-----

Electrical characteristics, at $T_j=25$ °C, unless otherwise specified

Static characteristics

Drain-source breakdown voltage ¹⁾	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0$ V, $I_D=250$ μA	600	-	-	V
Gate threshold voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=0$ V, $I_D=94$ μA	1.3	1.9	2.3	
Drain-source leakage current	$I_{\text{D}(\text{off})}$	$V_{\text{DS}}=600$ V, $V_{\text{GS}}=0$ V, $T_j=25$ °C	-	-	0.1	μA
		$V_{\text{DS}}=600$ V, $V_{\text{GS}}=0$ V, $T_j=150$ °C	-	-	5	
Gate-source leakage current	I_{GSS}	$V_{\text{GS}}=20$ V, $V_{\text{DS}}=0$ V	-	10	100	nA
Drain-source on-state resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}}=4.5$ V, $I_D=0.09$ A	-	30	45	Ω
		$V_{\text{GS}}=10$ V, $I_D=0.09$ A	-	28	45	
Transconductance	g_{fs}	$ V_{\text{DS}} >2 I_D R_{\text{DS}(\text{on})\text{max}},$ $I_D=0.075$ A	0.05	0.14	-	S

¹⁾ V_{DS} is zero-hour rated, see note at p.8

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0 \text{ V}, V_{DS}=25 \text{ V}, f=1 \text{ MHz}$	-	99	131	pF
Output capacitance	C_{oss}		-	7.6	11	
Reverse transfer capacitance	C_{rss}		-	3.1	4.4	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=300 \text{ V}, V_{GS}=10 \text{ V}, I_D=0.09 \text{ A}, R_G=6 \Omega$	-	14.0	20.0	ns
Rise time	t_r		-	38.0	57.0	
Turn-off delay time	$t_{d(off)}$		-	62.0	93	
Fall time	t_f		-	41.0	62	

Gate Charge Characteristics


Gate to source charge	Q_{gs}	$V_{DD}=400 \text{ V}, I_D=0.09 \text{ A}, V_{GS}=0 \text{ to } 10 \text{ V}$	-	0.32	0.43	nC
Gate to drain charge	Q_{gd}		-	1.4	2.1	
Gate charge total	Q_g		-	3.9	5.8	
Gate plateau voltage	$V_{plateau}$		-	3.3	-	

Reverse Diode


Diode continuous forward current	I_S	$T_A=25 \text{ }^\circ\text{C}$	-	-	0.09	A
Diode pulse current	$I_{S,pulse}$		-	-	0.36	
Diode forward voltage	V_{SD}	$V_{GS}=0 \text{ V}, I_F=0.09 \text{ A}, T_j=25 \text{ }^\circ\text{C}$	-	0.75	1.2	V
Reverse recovery time	t_{rr}	$V_R=300 \text{ V}, I_F=0.09 \text{ A}, di_F/dt=100 \text{ A}/\mu\text{s}$	-	246	370	ns
Reverse recovery charge	Q_{rr}		-	248	373	nC

1 Power dissipation

$$P_{\text{tot}} = f(T_A)$$



2 Drain current

$$I_D = f(T_A); V_{GS} \geq 10 \text{ V}$$


3 Safe operating area


$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$

parameter: t_p



4 Max. transient thermal impedance




$$Z_{\text{thJA}} = f(t_p)$$


parameter: $D = t_p/T$






5 Typ. output characteristics
 $I_D = f(V_{DS})$; $T_j = 25^\circ C$

parameter: V_{GS}

6 Typ. drain-source on resistance
 $R_{DS(on)} = f(I_D)$; $T_j = 25^\circ C$



parameter: V_{GS}

7 Typ. transfer characteristics
 $I_D = f(V_{GS})$; $|V_{DS}| > 2|I_D|R_{DS(on)max}$

8 Typ. forward transconductance
 $g_{fs} = f(I_D)$; $T_j = 25^\circ C$



9 Drain-source on-state resistance
 $R_{DS(on)} = f(T_j); I_D = 0.1 \text{ A}; V_{GS} = 10 \text{ V}$

10 Typ. gate threshold voltage
 $V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 94 \mu\text{A}$


parameter: I_D

11 Typ. capacitances
 $C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}; T_j = 25^\circ\text{C}$

12 Forward characteristics of reverse diode
 $I_F = f(V_{SD})$

parameter: T_j



13 Typ. gate charge
 $V_{GS} = f(Q_{gate})$; $I_D = 0.1 \text{ A}$ pulsed

parameter: V_{DD}

14 Drain-source breakdown voltage
 $V_{BR(DSS)} = f(T_j)$; $I_D = 250 \mu\text{A}$


Package Outline:

¹⁾Ejector pin markings \varnothing possible

Footprint:


Dimensions in mm

Packaging:

note:

Due to small size of the package, creeping currents between leads external to the package can occur in the application. Extra protection from contamination for the package (i.e. protective laquer) is necessary to maintain the values, specified in this document. Values given in this document are only valid for 0 hour lifetime, if no suitable external protection is applied.

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.