



### CAMPUS AND IN-BUILDING DIRECTIONAL ANTENNAS

DirectLink™ is a series of wall and mast mount directional antennas that has been designed to meet the most demanding needs of the contemporary wireless environment. DirectLink's attractive, UV resistant housings and mounts allow the antennas to be mounted anywhere in the campus or in-building environment. The antennas offer very precise and controllable pattern characteristics in frequencies starting with the 1710 MHz DCS band and continuing through the 5.725 GHz ISM band. All popular contemporary wireless system applications are covered with gain characteristics varying with the frequency.

All antennas in the series may be wall or mast mounted and all are available with a variety of flush and articulating mounts. Flush mounts allow the antenna to hug the wall for minimal visual impact. There are two available articulating mounts that allow the pattern to be directed while still maintaining minimal visual impact.

Standard antennas come with either TNC, SMA, or N female connectors and an integrated coaxial pigtail. Other connector and pigtail combinations are available upon request.

### FEATURES

- Indoor / outdoor
- Attractive styling
- Articulating
- Wall mountable

### APPLICATIONS

- Campuses
- In-building environments
- WiMAX

### global solutions: local support.™


Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

PARAMETERS	SPECIFICATIONS
Power	75 Watts (25 Watts at 5 GHz)
Polarization	Linear
Dimensions and Weight	
Standard wall mount –	5.70 x 3.81 x 1.50 in (14.48 x 9.68 x 3.80 cm) 5 oz (.14kg)
Articulating wall mount –	5.80 x 3.81 x 2.26 in (14.73 x 9.68 x 5.74 cm) 8 oz (.23 kg)
Connectors	SMA and TNC. Other connector types available on special request.
Mounting	Standard units for wall mounting. Mast mount bracket kits available. Custom mount configurations for volume users.
Cable	Low loss pigtail provided.



MODEL	FREQUENCY MHz	GAIN dBi	3 dB BWWIDTH		VSWR	F/B dB	CONNECTOR (FEMALE)	ARTICULATING VERSION
			E-PLANE	H-PLANE				
S2406MPC10NF*	2400-2500	6.5 dBi	65°	65°	1.5:1	20	N	Yes
S2307AMP10TNF	2300-2500	7.5	60°	65°	1.5:1	12	TNC	Yes
S2307MP10TNF	2300-2500	7.5	60°	65°	1.5:1	12	TNC	No
S2307AMP10SMF	2300-2500	7.5	60°	65°	1.5:1	12	SMA	Yes
S2307MP10SMF	2300-2500	7.5	60°	65°	1.5:1	12	SMA	No
S2307AMP10NF	2300-2500	7.5	60°	65°	1.5:1	12	N	Yes
S2307MP10NF	2300-2500	7.5	60°	65°	1.5:1	12	N	No

\*Right hand circular polarization



ANT-DS-S2307MP 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.