

111-25300

# HellermannTyton



Article Number: 111-25300

Description: Heavy-Duty Cable Tie, 22" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Base Data		
	Local Order Number	T255M0HIRX2
	Type	T255M
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 22" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	250.0lbs
	Minimum Tensile Strength (Metric)	1115.0N
	Length L (Imperial)	22.0"
	Length L (Metric)	560.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Variant	Inside Serrated
	Width W (Imperial)	0.5"
	Width W (Metric)	12.6mm
	Bundle Diameter Min. (Imperial)	0.49"
	Bundle Diameter Min. (Metric)	12.5mm
	Bundle Diameter Max. (Imperial)	6.3"
	Bundle Diameter Max. (Metric)	160.0mm

111-25300

**HellermannTyton**

Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-ZODZ2.E64139
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987