

111-25001

HellermannTyton



Article Number: 111-25001

Description: Heavy-Duty Cable Tie, 22.3" Long, 250lb Tensile Strength, PA66, Black, 25/pkg

Base Data		
	Local Order Number	T250M0X2
	Type	T250M
	Color	Black (BK)
	Features and Benefits	• Heavy duty design to offer higher tensile strength. • Buckle feature on head allows excess strap to be tucked away after installation.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 22.3" Long, 250lb Tensile Strength, PA66, Black, 25/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	250.0lbs
	Minimum Tensile Strength (Metric)	1115.0N
	Length L (Imperial)	22.3"
	Length L (Metric)	565.3mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.49"
	Width W (Metric)	12.5mm
	Bundle Diameter Min. (Imperial)	0.47"
	Bundle Diameter Min. (Metric)	12.0mm
	Bundle Diameter Max. (Imperial)	5.9"
	Bundle Diameter Max. (Metric)	150.0mm

111-25001



Product Dimensions	Thickness T (Metric)	1.9mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 62275
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	12kg