K MOPL K52 STAHL



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





For many years, the name Klippon® has stood for competence and quality in enclosures. The enclosures are ideal for turnkey customised solutions for standard industrial applications and for explosive-risk applications.

Improved products that meet all application requirements: this was Weidmüller's aim during the update of the Klippon® K housing series. Weidmüller delivers many types of aluminium enclosures; they are designed to fit precisely with a wide range of customer requirements and applications.

Our comprehensive product line provides the following advantages:

- Available in two different surfaces: natural and powdercoated (RAL 7001)
- Available normally with silicone or chloroprene gasket seal
- A uniform Torx-slotted screw head is used for over 19 different housing sizes.
- Mounting holes not within the sealed area
- High degree of protection: IP66, IP67 and IP68
- Impact resistance of up to 10 Joules
- The housings are certified by ATEX, GOST, GOST Ex, cULus, Russian Maritime Register, German Lloyd, as well as the empty housing standard.
- Alloy is resistant to salt water

• Standardised distributor housings with threaded holes and a variety of terminal configurations

General ordering data

| Туре | MOPL K52 STAHL | | |
|------------|---|--|--|
| Order No. | <u>3073100000</u> | | |
| Version | Mounting plate, Mounting Plate, Sheet steel, galvanised, 145 mm | | |
| GTIN (EAN) | 4008190858032 | | |
| Qty. | 1 pc(s). | | |

K MOPL K52 STAHL

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

| Dimensions and weights | | | | |
|----------------------------|-------------------------|----------------------------|---|--|
| | | | | |
| Width | 145 mm | Mounting dimension - width | 130 mm | |
| Net weight | 271 g | | | |
| General information | | | | |
| Material thickness | 2 mm | Material | Sheet steel, galvanised | |
| Impact resistance | 10.00 J | | Guideline de la constant de l | |
| General information on ac | cessories | | | |
| | | •• • • • • • • | | |
| Material | Sheet steel, galvanised | Material thickness | 2 mm | |
| Mounting dimension - width | 130 mm | Type of fixing | Screwed | |
| Classifications | | | | |
| ETIM 3.0 | EC000318 | UNSPSC | 31-16-23-03 | |
| eClass 5.1 | 27-18-92-07 | eClass 6.2 | 27-18-92-61 | |
| eClass 7.1 | 27-18-92-61 | | | |
| Approvals | | | | |
| Approvals | | | | |
| ROHS | Conform | | | |