



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

MCM1216

P-Channel Power MOSFET

Features

- Advanced trench MOSFET process technology
- Ultra low on-resistance with low gate charge
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking:1216


Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Parameter	Rating	Unit
V_{DS}	Drain-source Voltage	-12	V
I_D	Drain Current-Continuous	-16	A
I_{DM}	Pulsed Drain Current (note1)	-65	A
V_{GS}	Gate-source Voltage	± 8	V
P_D	Power Dissipation(note2, $T_a=25^\circ\text{C}$) Maximum Power Dissipation(note3, $T_c=25^\circ\text{C}$)	2.5 18	W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient(note4)	50	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance Junction to Case(note4)	6.9	$^\circ\text{C}/\text{W}$
T_J	Operating Junction Temperature	-55 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-55 to +150	$^\circ\text{C}$


Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. This test is performed with no heat sink at $T_a=25^\circ\text{C}$.
3. This test is performed with infinite heat sink at $T_c=25^\circ\text{C}$.
4. Surface mounted on FR4 board, $t \leq 10\text{S}$.

Equivalent Circuit



DFN2020-6J



- 1.DRAIN
- 2.DRAIN
- 3.GATE
- 4.SOURCE
- 5.DRAIN
- 6.DRAIN

DIM	Dimensions				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.028	.032	0.700	0.800	
B	0.008REF.		0.203REF.		
C	0.000	0.002	0.000	0.050	
D	0.076	0.082	1.924	2.076	
E	0.076	0.082	1.924	2.076	
F	0.031	0.039	0.800	1.000	
G	0.033	0.041	0.850	1.050	
H	0.008	0.016	0.200	0.400	
J	0.008	---	0.200	---	
K	0.018	0.026	0.460	0.660	
L	0.026TYP.		0.650TYP.		
M	0.010	0.014	0.250	0.350	
N	0.007	0.013	0.174	0.326	







ELECTRICAL CHARACTERISTICS(T_a=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-12			V
Gate-Body Leakage Current	I _{GSS}	V _{DS} = 0V, V _{GS} = ±8V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -12V, V _{GS} = 0V			-1	μA
On Characteristics (note 5)						
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.4	-0.7	-1	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} = -4.5V, I _D = -6.7A			21	mΩ
		V _{GS} = -2.5V, I _D = -6.2A			27	
Forward Transconductance	g _{FS}	V _{DS} = -10V, I _D = -6.7A		40		S
Dynamic Characteristics (note 6)						
Input Capacitance	C _{iSS}	V _{DS} = -10V, V _{GS} = 0V, f = 1MHz		2700		pF
Output Capacitance	C _{oSS}			680		
Reverse Transfer Capacitance	C _{rSS}			590		
Total Gate Charge	Q _g	V _{DS} = -6V, V _{GS} = -8V, I _D = -10A		60	100	nC
					35	
Gate-Source Charge	Q _{gs}	V _{DS} = -6V, V _{GS} = -4.5V, I _D = -10A		5		
Gate-Drain Charge	Q _{gd}			10		
Drain-Source Diode Characteristics						
Diode Forward Current (note 5)	I _S				-16	A
Diode Forward Voltage(note 4)	V _{SD}	V _{GS} = 0V, I _{SD} = -8A			-1.2	V

Notes:

- Pulse Test: Pulse With ≤300μs, Duty Cycle ≤2%.
- Guaranteed by design, not subject to production testing.

Typical Characteristics





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com