

170-03115



Article Number: 170-03115

Description: Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia, WH, 50 ft/reel

Base Data	Local Order Number	170-03115
	Type	BSHLR2010
	Color	White (WH)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>• Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li> <li>• Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul>
	Quantity Per	reel
	Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
	Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia, WH, 50 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		15.2m
Reel Length (imperial)		50.0ft
Bundle Diameter Min. (Imperial)		1.5"
Bundle Diameter Min. (Metric)		38.1mm
Bundle Diameter Max. (Imperial)		3.5"
Bundle Diameter Max. (Metric)		88.9mm
Diameter D (imperial)		2.0"
Nominal Diameter (Imperial)		2"
Nominal Diameter (Metric)		50.8mm
Material and Specifications	Material	Polyamide 6.6 (PA66E/CTFE)
	Material Shortcut	PA66E/CTFE

170-03115



Material and Specifications	Flammability	UL VW-1
	Operating Temperature	-103°F to +302°F (-75°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL2024
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50ft
	Package Quantity (Metric)	15.24m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	2.3lbs
	Weight (Metric)	1.04kg