

333-41504

Article Number: 333-41504



Description: Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 3/4", 19.1/6.0 Dia, PO, Black, 200 ft/reel

Base Data	Local Order Number	333-41504
	Type	TFN31 18/6
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters. • Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing). • Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels. • Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.
	Quantity Per	reel
	Product Description	TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing, and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.
	Short Description	Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 3/4", 19.1/6.0 Dia, PO, Black, 200 ft/reel
Product Dimensions	Length L (Imperial)	200.0ft
	Length L (Metric)	61.0m
	Shrink Ratio	3:1
	Trade Size	3/4 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 ¹⁴ Ω cm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	18mm
	Wall Thickness WT (Imperial)	.035"
	Wall Thickness WT (Metric)	0.90mm
	Recovered Diameter d (metric)	6.0mm

333-41504



Product Dimensions	Recovered Diameter d (imperial)	0.375"
	Supplied Diameter D (imperial)	0.75"
	Supplied Diameter D (metric)	18.0mm
Material and Specifications	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	Dielectric Strength (Metric)	>20 kV/mm
	Elongation at break	600%
	Flammability	UL 224 VW-1
	Halogenfree	No
	Shrink Temperature	+158 °F (+70 °C)
	Operating Temperature	-67°F to +275°F (-55°C to +135°C)
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 224
	UL Recognized (US)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		61m
Customs Number(Schedule B)		3926909987