

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set, B24, metal housing, consisting of sleeve housing 1411472, panel mounting base 1411331, EVO screw connection 1411440, pin contact insert 1407736, socket contact insert 1407735.



## Key Commercial Data

Flammability rating according to UL 94

Packing unit	1 pc
Weight per Piece (excluding packing)	800.0 g
Custom tariff number	85366990
Country of origin	Germany

## Technical data

#### General

Number of positions	24+PE	
Туре	B24	
Connection method	Push-in connection	
Cable exit	straight	
Degree of protection for housing	IP66	
	IP69K (ISO 20653:2013-02)	
	4	
	4X	
	12	
Connection method	Push-in connection	
Rated voltage (III/3)	500 V	
Rated surge voltage	6 kV	
Rated current	16 A	
Standards and Regulations		

V0



Articles in set

Contact insert - HC-B 24-I-PT-F - 1407735



HEAVYCON socket insert, B24 series, 24 + PE-pos., push-in connection

Contact insert - HC-B 24-I-PT-M - 1407736



HEAVYCON pin insert, B24 series, 24 + PE-pos., push-in connection

Cable gland - HC-B-G-M32-EC-AL - 1411440



EVO EMC cable gland with bayonet locking, B series, size M32, cable diameter: 14 - 21 mm

Housing - HC-EVO-B24-HHFD-EL-AL - 1411472



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B24, for double locking latch, height: 88 mm, without EVO screw connection.

Housing - HC-STA-B24-BWD-ELC-AL - 1411331



HEAVYCON B24 panel mounting base, with double locking latch, with flat gasket, salt-water-resistant aluminum, conductive profile gasket



## Classifications

### eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440101

#### ETIM

ETIM 4.0	EC002641
ETIM 5.0	EC002636

## Approvals

### Approvals

Approvals		
EAC		
Ex Approvals		
Approvals submitted		

### Approval details

EAC

## Drawings

#### Schematic diagram

13 ●	• 1
14 🖷	• 2
15 🖷	• 3
16 🖷	• 4
17 ●	• 5
18 🖷	• 6
19 🖷	• 7
20 🖷	• 8
21 🜒	• 9
22 ●	• 10
23 ●	• 11
24 🛛	• 12
l	

### Schematic diagram

10	0 13	
20	0 14	
30	O 15	
40	O 16	
50	0 17	
60	O 18	
70	O 19	
80	O 20	
90	0 21	
100	0 22	
110	0 23	
120	0 24	

Pin assignment, connection side, pin

Pin assignment, connection side, socket





Derating diagram

#### Dimensional drawing



32

Dimensional drawing

#### Dimensional drawing



Panel cutout

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com