



- △ MATERIAL AND FINISH:  
 SHELL: DIE CAST ALUMINUM ALLOY PER FED. SPEC QQ-A-591.  
 STANDARD FINISH: CADMIUM PLATE PER QQ-P-416, TYPE I,  
 CLASS 2 YELLOW CHROMATE CONVERSION.  
 INSERT RETENTION PLATE: ALUMINUM ALLOY, BLUE ANODIZE  
 PER MIL-A-8625.  
 SCREWS AND WASHERS: STAINLESS STEEL, PASSIVATED.  
 POLARIZING POSTS: STAINLESS STEEL, PASSIVATED.  
 POLARIZING NUTS: BRASS, CADMIUM PLATED.
2. KEYING IS SET IN POSITION "01".
- △ 921121-1, REV B AND DATE CODE XXYY, (WHERE  
 XX = WEEK, YY = YEAR) MARKED IN APPROX AREA SHOWN  
 WITH .047 [1.19] MIN HIGH CHARACTERS.

615040	1484650-1
AIRSHOW	PART NO.
PART NO. REF	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 7-30-03	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: INCHES		CHK D.FABY 4-26-06	NAME RECEPTACLE ASSY.SRINC 404,SPECIAL RM3R32C2P67P32C2P-0101 )200)	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D.FABY 4-28-06	RESTRICTED TO	
0 PLC ± -	1 PLC ± -	PRODUCT SPEC	SIZE A1	CAGE CODE 00779
2 PLC ± -	3 PLC ± -	APPLICATION SPEC	DRAWING NO 1484650	REV 0
4 PLC ± .010 [0.25]	ANGLES ± -	WEIGHT	CUSTOMER DRAWING	
MATERIAL	FINISH	SCALE 2:1 SHEET 1 OF 1		