

151-00651

HellermannTyton



Article Number: 151-00651

Description: Bundling Clip, Hole Diameter 6.2–6.8mm, Panel .7–18.0mm, PA66HIRHSUV, Natural, 2000/box

Base Data	
Local Order Number	151-00651
Type	TC6FT6LG
Color	Natural (NA)
Features and benefits	<ul style="list-style-type: none"> • Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly. • Initial fir tree serves as a locating feature for assistance in blind assembly applications.
Quantity Per	box
Product Description	HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.
Short Description	Bundling Clip, Hole Diameter 6.2–6.8mm, Panel .7–18.0mm, PA66HIRHSUV, Natural, 2000/box
Product Dimensions	
Length L (Imperial)	1.5"
Length L (Metric)	39.3mm
Fixation Method	Fir Tree
Width W (Imperial)	0.5"
Width W (Metric)	12.0mm
Height H (Imperial)	1.0"
Height H (Metric)	26.6mm
Height H2 (Imperial)	0.9"
Height H2 (Metric)	23.1mm
Panel Thickness Max. (Imperial)	0.71"
Panel Thickness Max. (Metric)	5.5mm
Panel Thickness Min. (Imperial)	0.03"
Panel Thickness Min. (Metric)	0.7mm
Mounting Hole Diameter D (Imperial)	0.26"

151-00651



Product Dimensions	Mounting Hole Diameter D (Metric)	6.2 - 6.8 mm
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.24"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	2000
	Package Quantity (Metric)	2000
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces