

Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B6, for single locking latch, height: 80 mm, without EVO screw connection.

Product Features

■ Flexible cable outlet direction, lateral or straight



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	160.0 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Height	80 mm
Width	44 mm
Length	60 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP69K (ISO 20653:2013-02)
Degree of protection of housing (NEMA)	4
	4X
	12
Ambient temperature (operation)	-40 °C 125 °C

General

Note	For contact inserts HC-B6, BB10, DD24, M Tall housings for extra large wiring space



Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Technical data

General

Size	B6		
Housing type	Sleeve housing		
Locking type	for single locking latch		
No. of cable outlets	1		
Cable exit	straight		
	Lateral		
Screw connection	none		
Housing material	Die-cast aluminum, salt water resistant		
Housing surface material	Uncoated		
The sleeve base housing must be supplemented wit connection. The EVO screw connection is available the creation of a straight or a lateral cable outlet. The connection is assembled by hand or using a pipe wr			

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 4.0	EC000437
ETIM 5.0	EC000437

Approvals

Approvals

Approvals

GL / EAC

Ex Approvals

Approvals submitted



Housing - HC-EVO-B06-HHFS-EL-AL - 1411447

Approvals


Approval details


I GL			
			1

EAC

Drawings

Dimensional drawing





Dimensional drawing

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com