

SOT23 SILICON PLANAR VARIABLE CAPACITANCE DIODE


ISSUE 4 – JANUARY 1998

BBY40

PIN CONFIGURATION



PARTMARKING DETAIL
BBY40 – S2



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Reverse Breakdown Voltage	V_{BR}	28.0			V	$I_R = 10\mu A$
Reverse current	I_R			10 1.0	nA μA	$V_R = 28V$ $V_R = 28V, T_{amb} = 60^{\circ}C$

TUNING CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Diode Capacitance	C_d	26.0 4.3		32.0 6.0	pF pF	$V_R = 3V, f=1MHz$ $V_R = 25V, f=1MHz$
Capacitance Ratio	C_d / C_d	5.0		6.5		$V_R = 3V/25V, f=1MHz$
Series Resistance	r_d		0.4	0.6	Ω	f=200MHz at the value of V_R at which $C_d=25pF$

Spice parameter data is available upon request for this device

BBY40

TYPICAL CHARACTERISTICS

