



# High Voltage IGBT Phase-Leg

ISOPLUS i4-PAC™ Package

FII24N170AH1

$I_{C25}$  = 18 A  
 $V_{CES}$  = 1700 V  
 $V_{CE(sat)}$  = 6.0 V



## IGBT

Symbol	Conditions	Maximum Ratings		
$V_{CES}$	$T_{VJ} = 25^\circ\text{C}$ to $150^\circ\text{C}$	1700	V	
$V_{GES}$	Continuous	$\pm 20$	V	
$V_{GEM}$	Transient	$\pm 30$	V	
$I_{C25}$	$T_C = 25^\circ\text{C}$	18	A	
$I_{C90}$	$T_C = 90^\circ\text{C}$	11	A	
$I_{CM}$		75	A	
<b>RBSOA</b>	$V_{GE} = +15 \text{ V}$ ; $R_G = 5 \Omega$ ; $T_{VJ} = 125^\circ\text{C}$ Clamped inductive load; $V_{clamp} = 1360\text{V}$	50	A	
<b>P<sub>c</sub></b>	$T_C = 25^\circ\text{C}$	140	W	

Symbol	Conditions	Characteristic Values		
		( $T_{VJ} = 25^\circ\text{C}$ unless otherwise specified)	min.	typ.
$V_{CE(sat)}$	$I_C = 16 \text{ A}$ ; $V_{GE} = 15 \text{ V}$ $T_{VJ} = 125^\circ\text{C}$		4.5 4.8	6.0 V V
$V_{GE(th)}$	$I_C = 250 \mu\text{A}$ ; $V_{GE} = V_{CE}$	3.0		5.0 V
$I_{CES}$	$V_{CE} = 0.8 V_{CES}$ ; $V_{GE} = 0 \text{ V}$ $T_{VJ} = 125^\circ\text{C}$			100 $\mu\text{A}$ 1.5 mA
$I_{GES}$	$V_{CE} = 0 \text{ V}$ ; $V_{GE} = \pm 20 \text{ V}$			$\pm 100 \text{ nA}$
$t_{d(on)}$	Inductive load $V_{CE} = 600 \text{ V}$ ; $I_C = 24 \text{ A}$ $V_{GE} = \pm 15 \text{ V}$ ; $R_G = 39 \Omega$	48		ns
$t_r$		60		ns
$t_{d(off)}$		200		ns
$t_f$		45		ns
$E_{off}$		1.1		mJ
$t_{d(on)}$	Inductive load, $T_{VJ} = 125^\circ\text{C}$ $V_{CE} = 600 \text{ V}$ ; $I_C = 24 \text{ A}$ $V_{GE} = \pm 15 \text{ V}$ ; $R_G = 39 \Omega$	40		ns
$t_r$		60		ns
$t_{d(off)}$		220		ns
$t_f$		55		ns
$E_{on}$		2.5		mJ
$E_{off}$		1.7		mJ

Note: All characteristic values and ratings refer to a single IGBT or diode except  $V_{CES}$ ,  $I_{CES}$  and  $C_{oes}$ .

## Features

- NPT³ IGBT
  - low saturation voltage
  - positive temperature coefficient for easy paralleling
  - fast switching
  - short tail current for optimized performance in resonant circuits
- SONIC-FRD™ diode
  - fast reverse recovery
  - low operating forward voltage
  - low leakage current
- ISOPLUS i4-PAC™ package
  - isolated back surface
  - low coupling capacity between pins and heatsink
  - enlarged creepage towards heatsink
  - application friendly pinout
  - low inductive current path
  - high reliability
  - industry standard outline
  - UL registered, E 72873

## Applications

- Single phaseleg
  - buck-boost chopper
- H-bridge
  - power supplies
  - induction heating
  - four quadrant DC drives
  - controlled rectifier
- Three phase bridge
  - AC drives
  - controlled rectifier

**IGBT**

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
$g_{fs}$	$I_C = 24 \text{ A}, V_{CE} = 10 \text{ V}$ , Note 2	10	16	S
$Q_g$		105		nC
$Q_{ge}$	$I_C = 16 \text{ A}, V_{GE} = 15 \text{ V}, V_{CE} = 0.5 V_{CES}$	17		nC
$Q_{gc}$		30		nC
$C_{ies}$		2400		pF
$C_{oes}$	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$	150		pF
$C_{res}$		30		pF
$R_{thJC}$		0.6	0.9	K/W
$R_{thCK}$				K/W

**Diode**


Symbol	Conditions	Maximum Ratings		
		min.	typ.	max.
$I_{F25}$	$T_C = 25^\circ\text{C}$	24	A	
$I_{F90}$	$T_C = 90^\circ\text{C}$	14	A	
Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
$V_F$	$I_F = 20 \text{ A}$ $T_{VJ} = 125^\circ\text{C}$	2.5 2.5	2.95	V V
$I_{RM}$	$I_F = 20 \text{ A}; di_F/dt = -450 \text{ A}/\mu\text{s}; T_{VJ} = 125^\circ\text{C}$	23	A	
$t_{rr}$	$V_R = 1200 \text{ V}; V_{GE} = 0 \text{ V}$	230		ns
$R_{thJC}$		1.6		K/W
$R_{thCS}$		0.6		K/W

**Component**

Symbol	Conditions	Maximum Ratings		
		min.	typ.	max.
$T_{VJ}$		-55...+150		$^\circ\text{C}$
$T_{stg}$		-55...+125		$^\circ\text{C}$
$V_{ISOL}$	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$	2500		V $\sim$
$F_c$	mounting force with clip	20...120		N

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
$C_p$	coupling capacity between shorted pins and mounting tab in the case	40		pF
$d_s, d_A$	pin - pin	1.7		mm
$d_s, d_A$	pin - backside metal	5.5		mm
<b>Weight</b>		9		g

IXYS MOSFETs and IGBTs are covered by 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 one or more of the following U.S. patents: 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463

**Outline Drawing**

SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.190	.205	4.83	5.21
A1	.102	.118	2.59	3.00
A2	.046	.085	1.17	2.16
b	.045	.055	1.14	1.40
b1	.058	.068	1.47	1.73
b2	.100	.110	2.54	2.79
C	.020	.029	0.51	0.74
D	.819	.840	20.80	21.34
E	.770	.799	19.56	20.29
e	.150 BSC		3.81 BSC	
L	.780	.840	19.81	21.34
L1	.083	.102	2.11	2.59
Q	.210	.244	5.33	6.20
R	.100	.180	2.54	4.57
S	.660	.690	16.76	17.53
T	.590	.620	14.99	15.75
U	.065	.080	1.65	2.03