Mini vibration motor SMD sku: 316040005



(images/product/316040005 1_02.jpg)

Operating condition

	•		
ltem		Specification	Condition remark
2-1	Rated voltage	1.3VDC	
2-2	Operating voltage	0.9~1.6VDC	
2-3	Rated load	Vibraton weight	As soecufued in outline drawing
2-4	Rated speed	9000±1500rpm	
2-5	Rotation	CW (clockwize)	
2-6	Motor Position	All position	
2-7	Operating environment	-20¬60°C	
		10¬90%Rh	
2-8	Storage environment	-40~80°C	No condensation of moisture
		5~95%Eh	
Measuremen codition			
ltem		Specification	Condition remark
3-1	Temperature	20±2°C	
3-2	Humidity	65±5%RH	
3-3	Motor position	Moror shaft horizontal	Lock the motor in a test fixture

All date are based on the measurement under the temperature of 20 $^{\circ}\mathrm{C}$ and humidity65% andRH.hower.the langes of temperature5-35°C and humiddity45-85%RH are to be applicable as long as long as no problems.

Overview

21

(http://www.seeedstudio.com/depot/Shenzhen-2U-t-11.html?ref=pinfo) Other Products From

(http://www.seeedstudio.com/depot/Others-m-24.html?ref=pinfo) Weight: 3 g

Designer: Others This Designer