High Current Fuses





Fuse Strips with Housing Rated 36V - SPECIAL PURPOSE FUSES (NOT INTENDED FOR AUTOMOTIVE or TRUCK APPLICATIONS)

Housed fuse strips with window for visual inspection of melting element. Current rating 30A - 150A, 36 VDC. 90° fork type lugs.

Specifications

Voltage Rating: 36 VDC
Interrupt Ratings: up to 375A
Operating Temperature Range: -40° to 125°C
Insulating Body: Out of ceramic
Metal Parts: Zinc-alloy
Complies with: DIN 72581/2



Ordering Information

Part Number	Package Size
156.5611.xxx1	50

Time-Current Characteristics

% of Rating	Opening Time Min / Max (s)
130	3,600 s / –
250	-/60 s


Ratings

Part Number	Current Rating (A)*	Typ. Voltage Drop (mV)	Material Thickness "S" (mm)
156.5611.5301	30	70	0.25
156.5611.5401	40	70	0.20
156.5611.5501	50	70	0.25
156.5611.5601	60	70	0.40
156.5611.5701	70	70	0.45
156.5611.5801	80	70	0.50
156.5611.6101	100	70	0.70
156.5611.6111	120	70	0.70
156.5611.6121	125	70	0.70
156.5611.6151	150	70	1.00

Corresponding holder see Section "Fuse Holders."


Dimensions

Dimensions in mm



Pre-Arcing Time-Limits

TIME-CURRENT CHARACTERISTIC CURVES



FI = 1.00 (max. operating current : 1.0 x I_{rat} at 23°C)

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.

 $^{^{*}}$ Metal parts in compliance with DIN 72581/2. Fuses with housings not mentioned in the standards.