

DIMENSIONS - inches (mm)

I J K L M 2.99 1.97 3.23 3.86 M4 (76) (50) (82) (98)

PART NUMBER G2G120

A B C D E F G H 6.85 7.48 3.23 3.23 4.53 3.94 3.27 2.68 (174) (190) (82) (82) (115) (100) (83) (68)

> N O P Q .28 3.94 5.20 17.72 (7) (100) (132) (450)

G2G120 Series Centrifugal

50

300

Single inlet centrifugal blower with brushless DC motor mounted inside the scroll housing for better performance and compact form/fit

Part Number	CFM @ 0	Curve	Volts	Voltage Range		dBA	Temp. Max C	Wgt. (oz)	Type Of Bearing	Features	Insul. Class
G2G120-AB17-52	130	1	24	16 to 28	40	58	60	72	Ball	Flange	R
G2G120-AR31-01	130	1	12	8 to 14	40	58	60	72	Ball	Flange	R
A	(FII)	-	- E	N	je.	1.50	100	200		cubic meters/ho 400 50	
		1 ITF	-111-	1	of wat	1.50					350 se
15		ا ا			nches of wate	1.20			+		300 0
	G 6	1160			Sure -	.90					250 88
		1		-0-	Static Pressure	.90					State oos
		ľ			Š	.60		+			150
				1				1			100

.30

0

50

100

150

200

Air Flow - CFM (cubic feet/minute)

250