

Absolute maximum ratings

(Ta=25°C)


Symbol	Ratings	Unit
V _{CBO}	35±5	V
V _{CEO}	35±5	V
V _{EBO}	6	V
I _c	3	A
I _b	1	A
P _T	4 (Ta=25°C) 20 (Tc=25°C)	W
T _j	150	°C
T _{stg}	-40 to +150	°C

Electrical characteristics

(Ta=25°C)


Symbol	Specification			Unit	Conditions
	min	typ	max		
I _{CBO}			10	μA	V _{CB} =30V
I _{EBO}			10	μA	V _{EB} =6V
V _{CEO}	30		40	V	I _c =25mA
h _{FE}	500				V _{CE} =4V, I _c =0.5A
V _{CE(sat)}			0.5	V	I _c =1A, I _b =5mA

■ Equivalent circuit diagram




Characteristic curves


I_c-V_{CE} Characteristics (Typical)




h_{FE}-I_c Characteristics (Typical)




h_{FE}-I_c Temperature Characteristics (Typical)




V_{CE(sat)}-I_c Characteristics (Typical)




V_{CE(sat)}-I_b Characteristics (Typical)




I_c-V_{BE} Temperature Characteristics (Typical)



θ_{ja}-PW Characteristics



P_T-Ta Characteristics



Safe Operating Area (SOA)

