

Dual N-Channel 30-V (D-S) MOSFET

PRODUCT SUMMARY				
	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A) ^a	Q _g (Typ.)
Channel 1	30	0.0145 at V _{GS} = 10 V	10.8	8.3
		0.0195 at V _{GS} = 4.5 V	9.3	
Channel 2	30	0.0265 at V _{GS} = 10 V	7.2	4
		0.036 at V _{GS} = 4.5 V	6.2	


FEATURES

- Halogen-free According to IEC 61249-2-21 Available
- TrenchFET[®] Power MOSFET
- 100 % R_g Tested





APPLICATIONS

- Logic DC/DC for Notebook PC



Ordering Information: Si4972DY-T1-E3 (Lead (Pb)-free)
Si4972DY-T1-GE3 (Lead (Pb)-free and Halogen-free)



ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted				
Parameter	Symbol	Channel 1	Channel 2	Unit
Drain-Source Voltage	V _{DS}	30		V
Gate-Source Voltage	V _{GS}	± 20		
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	10.8	7.2	A
	T _C = 70 °C	8.7	5.7	
	T _A = 25 °C	8.7 ^{b,c}	6.4 ^{b,c}	
	T _A = 70 °C	6.9 ^{b,c}	5.1 ^{b,c}	
Pulsed Drain Current (10 μs Pulse Width)	I _{DM}	20	20	A
Source-Drain Current Diode Current	T _C = 25 °C	2.5	2.1	
	T _A = 25 °C	1.6 ^{b,c}	1.6 ^{b,c}	
Pulsed Source-Drain Current	I _{SM}	20	20	mJ
Single Pulse Avalanche Current	L = 0.1 mH I _{AS}	15	6	
Avalanche Energy	E _{AS}	11	1.8	W
Maximum Power Dissipation	T _C = 25 °C	3.1	2.5	
	T _C = 70 °C	2.1	1.6	
	T _A = 25 °C	2.0 ^{b,c}	2.0 ^{b,c}	
	T _A = 70 °C	1.25 ^{b,c}	1.25 ^{b,c}	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150		°C

THERMAL RESISTANCE RATINGS						
Parameter	Symbol	Channel 1		Channel 2		Unit
		Typical	Maximum	Typical	Maximum	
Maximum Junction-to-Ambient ^{b, d}	t ≤ 10 s R _{thJA}	52	62.5	55	62.5	°C/W
Maximum Junction-to-Foot (Drain)	Steady R _{thJF}	32	40	40	50	

- Notes:
a. Based on T_C = 25 °C.
b. Surface mounted on 1" x 1" FR4 board.
c. t = 10 s.
d. Maximum under steady state conditions is 110 °C/W (Ch 1) and 120 °C/W (Ch 2).

SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions	Min.	Typ. ^a	Max.	Unit	
Static							
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	Ch 1	30		V	
		$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	Ch 2	30			
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = 250\text{ }\mu\text{A}$	Ch 1		35	mV/ $^\circ\text{C}$	
		$I_D = 250\text{ }\mu\text{A}$	Ch 2		35		
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$	$I_D = 250\text{ }\mu\text{A}$	Ch 1		- 6.5		
		$I_D = 250\text{ }\mu\text{A}$	Ch 2		- 6.5		
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	Ch 1	1.5	3.0	V	
		$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	Ch 2	1.5	3.0		
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$	Ch 1		100	nA	
			Ch 2		100		
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$	Ch 1		1	μA	
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$	Ch 2		1		
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}, T_J = 55\text{ }^\circ\text{C}$	Ch 1		10		
		$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}, T_J = 55\text{ }^\circ\text{C}$	Ch 2		10		
On-State Drain Current ^b	$I_{D(on)}$	$V_{DS} = 5\text{ V}, V_{GS} = 10\text{ V}$	Ch 1	10		A	
		$V_{DS} = 5\text{ V}, V_{GS} = 10\text{ V}$	Ch 2	10			
Drain-Source On-State Resistance ^b	$R_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 6\text{ A}$	Ch 1		0.012	0.0145	Ω
		$V_{GS} = 10\text{ V}, I_D = 4.5\text{ A}$	Ch 2		0.022	0.0265	
		$V_{GS} = 4.5\text{ V}, I_D = 5.6\text{ A}$	Ch 1		0.016	0.0195	
		$V_{GS} = 4.5\text{ V}, I_D = 4\text{ A}$	Ch 2		0.030	0.036	
Forward Transconductance ^b	g_{fs}	$V_{DS} = 15\text{ V}, I_D = 6\text{ A}$	Ch 1		27	S	
		$V_{DS} = 15\text{ V}, I_D = 4.5\text{ A}$	Ch 2		20		
Dynamic^a							
Input Capacitance	C_{iss}	Channel 1 $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$ Channel 2 $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$	Ch 1		1080	pF	
			Ch 2		515		
Output Capacitance	C_{oss}		Ch 1		170		
			Ch 2		91		
Reverse Transfer Capacitance	C_{rss}		Ch 1		72		
			Ch 2		38		
Total Gate Charge	Q_g	$V_{DS} = 15\text{ V}, V_{GS} = 10\text{ V}, I_D = 5\text{ A}$	Ch 1		18.5	28	nC
		$V_{DS} = 15\text{ V}, V_{GS} = 10\text{ V}, I_D = 5\text{ A}$	Ch 2		9.6	15	
		Channel 1 $V_{DS} = 15\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 5\text{ A}$	Ch 1		8.3	13	
			Ch 2		4	6	
Gate-Source Charge	Q_{gs}	Channel 2 $V_{DS} = 15\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 5\text{ A}$	Ch 1		3.9		
			Ch 2		1.9		
Gate-Drain Charge	Q_{gd}	Channel 1 $V_{DS} = 15\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 5\text{ A}$	Ch 1		2.7		
			Ch 2		1.3		
Gate Resistance	R_g	$f = 1\text{ MHz}$	Ch 1		2.5	3.8	Ω
			Ch 2		2.9	4.4	




SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions	Min.	Typ. ^a	Max.	Unit	
Dynamic^a							
Turn-On Delay Time	$t_{d(on)}$	Channel 1 $V_{DD} = 15\text{ V}, R_L = 3\ \Omega$ $I_D \cong 5\text{ A}, V_{GEN} = 10\text{ V}, R_g = 1\ \Omega$	Ch 1		12	18	ns
			Ch 2		10	15	
Rise Time	t_r		Ch 1		55	83	
			Ch 2		60	90	
Turn-Off Delay Time	$t_{d(off)}$	Channel 2 $V_{DD} = 15\text{ V}, R_L = 3\ \Omega$ $I_D \cong 5\text{ A}, V_{GEN} = 10\text{ V}, R_g = 1\ \Omega$	Ch 1		30	45	
			Ch 2		22	33	
Fall Time	t_f		Ch 1		7	11	
			Ch 2		6	9	
Turn-On Delay Time	$t_{d(on)}$	Channel 1 $V_{DD} = 15\text{ V}, R_L = 3\ \Omega$ $I_D \cong 5\text{ A}, V_{GEN} = 4.5\text{ V}, R_g = 1\ \Omega$	Ch 1		120	180	
			Ch 2		108	162	
Rise Time	t_r		Ch 1		150	225	
			Ch 2		130	195	
Turn-Off Delay Time	$t_{d(off)}$	Channel 2 $V_{DD} = 15\text{ V}, R_L = 3\ \Omega$ $I_D \cong 5\text{ A}, V_{GEN} = 4.5\text{ V}, R_g = 16\ \Omega$	Ch 1		29	44	
			Ch 2		19	29	
Fall Time	t_f		Ch 1		13	20	
			Ch 2		26	39	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25\text{ }^\circ\text{C}$	Ch 1		2.5	A	
			Ch 2		2.1		
Pulse Diode Forward Current ^a	I_{SM}		Ch 1		20		
			Ch 2		20		
Body Diode Voltage	V_{SD}	$I_S = 1.6\text{ A}$	Ch 1	0.77	1.2	V	
			Ch 2	0.79	1.2		
Body Diode Reverse Recovery Time	t_{rr}	Channel 1 $I_F = 2\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$	Ch 1	21	42	ns	
			Ch 2	18	36		
Body Diode Reverse Recovery Charge	Q_{rr}		Ch 1	15	30	nC	
			Ch 2	11	22		
Reverse Recovery Fall Time	t_a	Channel 2 $I_F = 2\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$	Ch 1	13		ns	
			Ch 2	11			
Reverse Recovery Rise Time	t_b		Ch 1	8			
			Ch 2	7			

Notes:


- a. Guaranteed by design, not subject to production testing.
- b. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics (Ch 1)




Transfer Characteristics (Ch 1)




On-Resistance vs. Drain Current and Gate Voltage (Ch 1)



Capacitance (Ch 1)








Gate Charge (Ch 1)






On-Resistance vs. Junction Temperature (Ch 1)

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted









Normalized Thermal Transient Impedance, Junction-to-Ambient (Ch 1)




Normalized Thermal Transient Impedance, Junction-to-Case (Ch 1)


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage (Ch 2)




On-Resistance vs. Gate-to-Source Temperature (Ch 2)



Threshold Voltage (Ch 2)




Single Pulse Power, Junction-to-Ambient (Ch 2)




Safe Operating Area, Junction-to-Ambient (Ch 2)
* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



T_C - Case Temperature (°C)
Current Derating* (Ch 2)




T_C - Case Temperature (°C)
Power Derating, Junction-to-Foot (Ch 2)




T_A - Ambient Temperature (°C)
Power Derating, Junction-to-Ambient (Ch 2)

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Normalized Thermal Transient Impedance, Junction-to-Ambient (Ch 2)



Normalized Thermal Transient Impedance, Junction-to-Case (Ch 2)

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?73849.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.