

1 | 2

NOTE:

1. MATERIAL, HOUSING: HIGH TEMP THERMAL PLASTIC, UL94-VO

TERMINAL: COPPER ALLOY

2. FINISH:


TERMINAL: GOLD AT CONTACT,
G/F OVER 1UM(40u")MIN NI OVER ALL


3. SPEC.:
PRODUCT SPEC: GS-12-629
PACKING SPEC: GS-14-1517

4. THE HSG. WILL WITHSTAND EXPOSURE TO 260C

PEAK TEMP. FOR 10 SEC. IN A WAVE SOLDER APPLICATION.

5. MATING SIDE LENGTH: 2.5MM MIN.





mat	'l. cod	е				tolerances unless otherwise specified						CUSTOMER			1	FÇ	,						
ltr	ecn r	n no dr		date				.X ± 0.38				COPY				-						nect.c	om
Α	T10-0	-0065 S.LIN		10'-5-20		linea	· 🗀	.XX ± 0.25				projection		title 1.27X1.27MM BTB STACK HD VT TH									
								.XXX ± 0.15			Ψ 7		VT, TH										
						angle	s	0° ±2°					۷١,	ΙП									
							STE	Sterling Lin		10'-5-20			,					code	е				
						engr	STE	STERLING LIN		10'-5-20 10'-5-20					size	dwg no					TW	/N	
						chr	STE					scale		1 1	20021814 she					shee	et		
						appd	GAF	GARY HSIEH		10'-5-20		NA			A4	4 20021014				4	1 of		
she	et r	revision		Α																			
inde	ex s	sheet		1																			
-													cone code										

3

PDM: Rev:A 3 STATUS: Released Printed: Jun 01, 2010