

Model #: S404-006

6-ft. SCSI Double Shielded Cable (HD68 M/M)

Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors



Description

Multi-platform SCSI III external peripheral cable HD68M/M. This 6ft cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

System Requirements

Any external SCSI device or host controller card requiring HD68 interface

Package Includes

• 6-ft. SCSI cable HD68M to HD68M double shielded

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

Specifications

OVERVIEW		
Intended Application	Connecting Drives	
Cable Type	SCSI	
Model Type	SCSI III External	
INPUT		
Cable Length (ft.)	6	

Cable Length (m)	1.83			
UPC Codes				
Unit Carton UPC#	037332014122			
PHYSICAL				
Color	Beige			
Style	SCSI			
CONNECTIONS				
Connector A	•			
Connector B	0 (
WARRANTY				
Product Warranty Period (Worldwide)	Lifetime limited warranty			

Related Items

Optional Products

Related Model	Description	Qty.
S140-000	External SCSI U320 LVD/SE Active Terminator (HD68 M)	1
S450-010	6-ft. SCSI Ultra2/U160/U320 LVD Cable (HD68 M/M w/thumbscrews)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModeIID=2393.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.