

## SUMMARY

### # Wires

Low	0
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

*Image is for illustrative purpose only*

### Download

[Request a quote](#)

[Catalog](#)

Series	SP
Termination type	
IP rating	50
Cable Ø	6.60 - 7.50 mm
Matching parts	SRN.M13.GLL.7G
Status	
Alternative part	

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	SA*: Straight plug, key (N) or keys (P, S and T), with grey cable collet
Keying	3 key (alpha=30, plug: male contacts, receptacle: female contacts)
Housing Material	
Cable Fixing	∅ 6.6 - 7.5 mm
Variant	G : Gray collet nut

### Performance

Configuration	
Insulator	
Rated Current	4.0 Amps

### Specifications

Test voltage (kV rms) Contact-contact:	1.05
Air clearance min. (mm) or Creepage distance min. (mm):	0.50

### Others

IP Rating:	50
------------	----

---

# DRAWINGS

## Draws

## Dimensions

	A	L
mm.	16.5	46
in.	0,65	1,81

---

# RECOMMENDED BY LEMO

## Tools

Crimp Tool: DPC.91.701.V

## Cables