

115-42002



Article Number: 115-42002

Description: Releasable Cable Tie, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Base Data	Local Order Number	SR255S0HIHSUVX2
	Type	SR255S
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Impact-resistant, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li> <li>• Special design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Releasable Cable Tie, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		1115.0N
Length L (Imperial)		8.9"
Length L (Metric)		225.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		Yes
Width W (Imperial)		0.5"
Width W (Metric)		12.6mm
Cable Tie Width Max. (Imperial)		0.49"
Cable Tie Width Max. (Metric)		12.5mm
Bundle Diameter Min. (Imperial)		0.51"
Bundle Diameter Min. (Metric)		13.0mm

115-42002



Product Dimensions	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.0mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987