

Ultrafast recovery diode

Main product characteristics

| | |
|----------------------|--------|
| $I_{F(AV)}$ | 8 A |
| V_{RRM} | 400 V |
| $T_j(\text{max})$ | 175° C |
| $V_F(\text{typ})$ | 0.9 V |
| $t_{rr}(\text{typ})$ | 25 ns |


Features and benefits

- Very low switching losses
- High frequency and high pulsed current operation
- High junction temperature
- Insulated packages
 - TO-220AC Ins
Electrical insulation = 2500 V RMS
Capacitance = 7 pF
 - TO-220FPAC
Electrical insulation = 1500 V RMS
Capacitance = 12 pF

Description

The STTH8R04 series uses ST's new 400 V planar Pt doping technology. The STTH8R04 is specially suited for switching mode base drive and transistor circuits.

Packaged in through-the-hole and surface mount packages, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection.



Order codes

| Part Number | Marking |
|--------------|------------|
| STTH8R04D | STTH8R04D |
| STTH8R04DI | STTH8R04DI |
| STTH8R04FP | STTH8R04FP |
| STTH8R04G | STTH8R04G |
| STTH8R04G-TR | STTH8R04G |

1 Characteristics

Table 1. Absolute ratings (limiting values at 25° C, unless otherwise specified)

| Symbol | Parameter | | | Value | Unit |
|---------------------|-----------------------------------------|-----------------------------------|-------------------------------------------|-------------------------------------------------------------------------------|------|
| V _{RRM} | Repetitive peak reverse voltage | | | 400 | V |
| V _{RSM} | Repetitive peak reverse voltage | | | 400 | V |
| I _{F(RMS)} | RMS forward current | | TO-220AC / D ² PAK / TO220FPAC | 30 | A |
| | | | TO220AC Ins | 20 | |
| I _{F(AV)} | Average forward current, $\delta = 0.5$ | | TO-220AC / D ² PAK | T _c = 145° C T _c = 110° C T _c = 115° C | 8 |
| | | | TO220FPAC | | |
| | | | TO220AC Ins | | |
| I _{FRM} | Repetitive peak forward current | | t _p = 10 µs, F = 1 kHz | 165 | A |
| I _{FSM} | Surge non repetitive forward current | t _p = 10 ms Sinusoidal | | | 120 |
| T _{stg} | Storage temperature range | | | -65 to +175 | °C |
| T _j | Operating junction temperature range | | | -40 to +175 | °C |

Table 2. Thermal parameters

| Symbol | Parameter | | | Value | Unit |
|----------------------|------------------|-------------------------------|-----|-------|------|
| R _{th(j-c)} | Junction to case | TO-220AC / D ² PAK | 2.5 | °C/W | |
| | | TO220FPAC | 6 | | |
| | | TO220AB Ins | 5.5 | | |

Table 3. Static electrical characteristics

| Symbol | Parameter | Test conditions | | Min. | Typ | Max. | Unit |
|-------------------------------|-------------------------|-------------------------|-----------------------------------|------|------|------|------|
| I _R ⁽¹⁾ | Reverse leakage current | T _j = 25° C | V _R = V _{RRM} | | | 10 | µA |
| | | T _j = 125° C | | | 10 | 100 | |
| V _F ⁽²⁾ | Forward voltage drop | T _j = 25° C | I _F = 8 A | | | 1.5 | V |
| | | T _j = 100° C | | | 1.05 | 1.3 | |
| | | T _j = 150° C | | | 0.9 | 1.1 | |

1. Pulse test: t_p = 5 ms, δ < 2 %2. Pulse test: t_p = 380 µs, δ < 2 %

To evaluate the conduction losses use the following equation:

$$P = 0.83 \times I_{F(AV)} + 0.034 \times I_{F(RMS)}^2$$

Table 4. Dynamic characteristics

| Symbol | Parameter | Test conditions | Min | Typ | Max | Unit |
|----------|--------------------------|-----------------------------------------------------------------------------------------------------------------|-----|-----|-----|------|
| t_{rr} | Reverse recovery time | $I_F = 1 \text{ A}, dI_F/dt = -50 \text{ A}/\mu\text{s}, V_R = 30 \text{ V}, T_j = 25^\circ \text{C}$ | | 35 | 50 | ns |
| | | $I_F = 1 \text{ A}, dI_F/dt = -100 \text{ A}/\mu\text{s}, V_R = 30 \text{ V}, T_j = 25^\circ \text{C}$ | | 25 | 35 | |
| I_{RM} | Reverse recovery current | $I_F = 8 \text{ A}, dI_F/dt = -200 \text{ A}/\mu\text{s}, V_R = 320 \text{ V}, T_j = 125^\circ \text{C}$ | | 5.5 | 8 | A |
| S | Softness factor | $I_F = 8 \text{ A}, dI_F/dt = -200 \text{ A}/\mu\text{s}, V_R = 320 \text{ V}, T_j = 125^\circ \text{C}$ | | 0.4 | | |
| t_{fr} | Forward recovery time | $I_F = 8 \text{ A}, dI_F/dt = 100 \text{ A}/\mu\text{s}, V_{FR} = 1.1 \times V_{Fmax}, T_j = 25^\circ \text{C}$ | | | 150 | ns |
| V_{FP} | Forward recovery voltage | $I_F = 8 \text{ A}, dI_F/dt = 100 \text{ A}/\mu\text{s}$ | | 2.9 | | V |





Figure 1. Conduction losses versus average current**Figure 2. Forward voltage drop versus forward current****Figure 3. Relative variation of thermal impedance junction to case versus pulse duration****Figure 4. Relative variation of thermal impedance junction to case versus pulse duration TO-220FPAB**

Figure 5. Peak reverse recovery current versus dI_F/dt (typical values)




Figure 6. Reverse recovery time versus dI_F/dt (typical values)




Figure 7. Reverse recovery charges versus dI_F/dt (typical values)




Figure 8. Thermal resistance junction to ambient versus copper surface under tab (Epoxy printed circuit board FR4, $e_{CU}=35\mu m$)




Figure 9. Relative variations of dynamic parameters versus junction temperature




Figure 10. Transient peak forward voltage versus dI_F/dt (typical values)




Figure 11. Forward recovery time versus dI_F/dt (typical values)





Figure 12. Junction capacitance versus reverse voltage applied (typical values)



2 Package information

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)
- Recommended torque value: 0.55 Nm (TO-220AC, TO-220AC Ins, TO-220FPAC)
- Maximum torque value: 0.70 Nm (TO-220AC, TO-220AC Ins, TO-220FPAC)

Table 5. D²PAK dimensions

| Ref. | Dimensions | | | |
|------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.40 | 4.60 | 0.173 | 0.181 |
| A1 | 2.49 | 2.69 | 0.098 | 0.106 |
| A2 | 0.03 | 0.23 | 0.001 | 0.009 |
| B | 0.70 | 0.93 | 0.027 | 0.037 |
| B2 | 1.14 | 1.70 | 0.045 | 0.067 |
| C | 0.45 | 0.60 | 0.017 | 0.024 |
| C2 | 1.23 | 1.36 | 0.048 | 0.054 |
| D | 8.95 | 9.35 | 0.352 | 0.368 |
| E | 10.00 | 10.40 | 0.393 | 0.409 |
| G | 4.88 | 5.28 | 0.192 | 0.208 |
| L | 15.00 | 15.85 | 0.590 | 0.624 |
| L2 | 1.27 | 1.40 | 0.050 | 0.055 |
| L3 | 1.40 | 1.75 | 0.055 | 0.069 |
| M | 2.40 | 3.20 | 0.094 | 0.126 |
| R | 0.40 typ. | | 0.016 typ. | |
| V2 | 0° | 8° | 0° | 8° |

Figure 13. D²PAK footprint (dimensions in mm)




Table 6. TO-220AC dimensions

| Ref. | Dimensions | | | |
|---------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.40 | 4.60 | 0.173 | 0.181 |
| C | 1.23 | 1.32 | 0.048 | 0.051 |
| D | 2.40 | 2.72 | 0.094 | 0.107 |
| E | 0.49 | 0.70 | 0.019 | 0.027 |
| F | 0.61 | 0.88 | 0.024 | 0.034 |
| F1 | 1.14 | 1.70 | 0.044 | 0.066 |
| G | 4.95 | 5.15 | 0.194 | 0.202 |
| H2 | 10.00 | 10.40 | 0.393 | 0.409 |
| L2 | 16.40 typ. | | 0.645 typ. | |
| L4 | 13.00 | 14.00 | 0.511 | 0.551 |
| L5 | 2.65 | 2.95 | 0.104 | 0.116 |
| L6 | 15.25 | 15.75 | 0.600 | 0.620 |
| L7 | 6.20 | 6.60 | 0.244 | 0.259 |
| L9 | 3.50 | 3.93 | 0.137 | 0.154 |
| M | 2.6 typ. | | 0.102 typ. | |
| Diam. I | 3.75 | 3.85 | 0.147 | 0.151 |

Table 7. TO-220FPAC dimensions

| Ref. | Dimensions | | | |
|------|-------------|------|-----------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.4 | 4.6 | 0.173 | 0.181 |
| B | 2.5 | 2.7 | 0.098 | 0.106 |
| D | 2.5 | 2.75 | 0.098 | 0.108 |
| E | 0.45 | 0.70 | 0.018 | 0.027 |
| F | 0.75 | 1 | 0.030 | 0.039 |
| F1 | 1.15 | 1.70 | 0.045 | 0.067 |
| G | 4.95 | 5.20 | 0.195 | 0.205 |
| G1 | 2.4 | 2.7 | 0.094 | 0.106 |
| H | 10 | 10.4 | 0.393 | 0.409 |
| L2 | 16 Typ. | | 0.63 Typ. | |
| L3 | 28.6 | 30.6 | 1.126 | 1.205 |
| L4 | 9.8 | 10.6 | 0.386 | 0.417 |
| L5 | 2.9 | 3.6 | 0.114 | 0.142 |
| L6 | 15.9 | 16.4 | 0.626 | 0.646 |
| L7 | 9.00 | 9.30 | 0.354 | 0.366 |
| Dia. | 3.00 | 3.20 | 0.118 | 0.126 |

Table 8. TO-220AC Ins. dimensions

| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 15.20 | | 15.90 | 0.598 | | 0.625 |
| a1 | | 3.75 | | | 0.147 | |
| a2 | 13.00 | | 14.00 | 0.511 | | 0.551 |
| B | 10.00 | | 10.40 | 0.393 | | 0.409 |
| b1 | 0.61 | | 0.88 | 0.024 | | 0.034 |
| b2 | 1.23 | | 1.32 | 0.048 | | 0.051 |
| C | 4.40 | | 4.60 | 0.173 | | 0.181 |
| c1 | 0.49 | | 0.70 | 0.019 | | 0.027 |
| c2 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| e | 4.80 | | 5.40 | 0.189 | | 0.212 |
| F | 6.20 | | 6.60 | 0.244 | | 0.259 |
| ØI | 3.75 | | 3.85 | 0.147 | | 0.151 |
| I4 | 15.80 | 16.40 | 16.80 | 0.622 | 0.646 | 0.661 |
| L | 2.65 | | 2.95 | 0.104 | | 0.116 |
| I2 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| M | | 2.60 | | | 0.102 | |

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

3 Ordering information

| Part Number | Marking | Package | Weight | Base qty | Delivery mode |
|--------------|------------|--------------------|--------|----------|---------------|
| STTH8R04D | STTH8R04D | TO-220AC | 1.86 g | 50 | Tube |
| STTH8R04DI | STTH8R04DI | TO-220 Ins | 2.3 g | 50 | Tube |
| STTH8R04FP | STTH8R04FP | TO220FPAC | 1.64 g | 50 | Tube |
| STTH8R04G | STTH8R04G | D ² PAK | 1.48 g | 50 | Tube |
| STTH8R04G-TR | STTH8R04G | D ² PAK | 1.48 g | 1000 | Tape and reel |

4 Revision history

| Date | Revision | Description of Changes |
|-------------|----------|------------------------|
| 11-Mar-2007 | 1 | First issue. |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com