

## **CS1601 120W, High-efficiency PFC Demonstration Board**

### **Features**


- ❑ Line Voltage Range: 108 to 305 VACrms
- ❑ Output Voltage ( $V_{LINK}$ ): 460V
- ❑ Rated  $P_{out}$ : 115W
- ❑ Efficiency: 95% @ 115W
- ❑ Spread Spectrum Switching Frequency
- ❑ Integrated Digital Feedback Control
- ❑ Low Component Count

### **General Description**

The CDB1601-120W board demonstrates the performance of the CS1601 digital PFC controller as a stand-alone unit. This board is 95% efficient at full load, and has been tailored for use with a resonant second stage to power up to two T5 fluorescent lamps for a maximum output power of 108W. A resonant second stage driver efficiency of 94% is assumed for this application.

### **ORDERING INFORMATION**

CDB1601-120W Customer Demonstration Board



Actual Size:

258 mm x 43 mm  
8.16 in x 1.7 in



## IMPORTANT SAFETY INSTRUCTIONS

**Read and follow all safety instructions prior to using this demonstration board.**

This Engineering Evaluation Unit or Demonstration Board must only be used for assessing IC performance in a laboratory setting. This product is not intended for any other use or incorporation into products for sale.

This product must only be used by qualified technicians or professionals who are trained in the safety procedures associated with the use of demonstration boards.

### **⚠ DANGER Risk of Electric Shock**

- The direct connection to the AC power line and the open and unprotected boards present a serious risk of electric shock and can cause serious injury or death. Extreme caution needs to be exercised while handling this board.
- Avoid contact with the exposed conductor or terminals of components on the board. High voltage is present on exposed conductor and it may be present on terminals of any components directly or indirectly connected to the AC line.
- Dangerous voltages and/or currents may be internally generated and accessible at various points across the board.
- Charged capacitors store high voltage, even after the circuit has been disconnected from the AC line.
- Make sure that the power source is off before wiring any connection. Make sure that all connectors are well connected before the power source is on.
- Follow all laboratory safety procedures established by your employer and relevant safety regulations and guidelines, such as the ones listed under, OSHA General Industry Regulations - Subpart S and NFPA 70E.

**⚠ WARNING** Suitable eye protection must be worn when working with or around demonstration boards. Always comply with your employer's policies regarding the use of personal protective equipment.

**⚠ WARNING** All components, heat sinks or metallic parts may be extremely hot to touch when electrically active.

**⚠ WARNING** Heatsinking is required for Q4. The end product should use tar pitch or an equivalent compound for this purpose. For lab evaluation purposes, a fan is recommended to provide adequate cooling.

---

## Contacting Cirrus Logic Support

For all product questions and inquiries contact a Cirrus Logic Sales Representative. To find the one nearest to you go to [www.cirrus.com](http://www.cirrus.com)

---

### IMPORTANT NOTICE

Cirrus Logic, Inc. and its subsidiaries ("Cirrus") believe that the information contained in this document is accurate and reliable. However, the information is subject to change without notice and is provided "AS IS" without warranty of any kind (express or implied). Customers are advised to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgment, including those pertaining to warranty, indemnification, and limitation of liability. No responsibility is assumed by Cirrus for the use of this information, including use of this information as the basis for manufacture or sale of any items, or for infringement of patents or other rights of third parties. This document is the property of Cirrus and by furnishing this information, Cirrus grants no license, express or implied under any patents, mask work rights, copyrights, trademarks, trade secrets or other intellectual property rights. Cirrus owns the copyrights associated with the information contained herein and gives consent for copies to be made of the information only for use within your organization with respect to Cirrus integrated circuits or other products of Cirrus. This consent does not extend to other copying such as copying for general distribution, advertising or promotional purposes, or for creating any work for resale.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). CIRRUSS PRODUCTS ARE NOT DESIGNED, AUTHORIZED OR WARRANTED FOR USE IN PRODUCTS SURGICALLY IMPLANTED INTO THE BODY, AUTOMOTIVE SAFETY OR SECURITY DEVICES, LIFE SUPPORT PRODUCTS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF CIRRUSS PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK AND CIRRUSS DISCLAIMS AND MAKES NO WARRANTY, EXPRESS, STATUTORY OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE, WITH REGARD TO ANY CIRRUSS PRODUCT THAT IS USED IN SUCH A MANNER. IF THE CUSTOMER OR CUSTOMER'S CUSTOMER USES OR PERMITS THE USE OF CIRRUSS PRODUCTS IN CRITICAL APPLICATIONS, CUSTOMER AGREES, BY SUCH USE, TO FULLY INDEMNIFY CIRRUSS, ITS OFFICERS, DIRECTORS, EMPLOYEES, DISTRIBUTORS AND OTHER AGENTS FROM ANY AND ALL LIABILITY, INCLUDING ATTORNEYS' FEES AND COSTS, THAT MAY RESULT FROM OR ARISE IN CONNECTION WITH THESE USES.

Cirrus Logic, Cirrus, and the Cirrus Logic logo designs are trademarks of Cirrus Logic, Inc. All other brand and product names in this document may be trademarks or service marks of their respective owners.

## 1. INTRODUCTION

The CS1601 is a high-performance Variable Frequency Discontinuous Conduction Mode (VF-DCM), active Power Factor Correction (PFC) controller, optimized to deliver the lowest PFC system cost for electronic ballast applications. The CS1601 uses a digital control algorithm that is optimized for high efficiency and near unity power factor over a wide input voltage range (108-305 VAC).

The CS1601 uses an adaptive digital control algorithm. Both the ON time and the switching frequency are varied on a cycle-by-cycle basis over the entire AC line to achieve close to unity power factor. The variation in switching frequency also provides a spread frequency spectrum, thus minimizing the conducted EMI filtering requirements.

The feedback loop is closed through an integrated digital control system within the IC. Protection features such as overvoltage, overcurrent, overpower, open circuit, overtemperature, and brownout help protect the device during abnormal transient conditions. Details of these features are provided in the CS1601 data sheet.

The CDB1601-120W board demonstrates the performance of the CS1601 over a wide input voltage range of 108 to 305 VAC, typically seen in universal input ballast applications. This board has been designed for a 460 V, 115 W full load output application.

Extreme caution needs to be exercised while handling this board. This board is to be powered up by trained professionals only.

Prior to applying AC power to the CDB1601-120W board, the CS1601 needs to be biased using an external 13 VDC power supply, applied across pins 1 and 3 of terminal block J5. Terminal block J6 is used to connect the AC line. The load is connected to J7. As a safety measure, jumper J1 is provided as a means to apply a small resistive load (200 kΩ minimum) to rapidly discharge the output capacitors. Other jumpers and test points are provided to evaluate the behavior of the IC and the various sections of the design.



**Figure 1. Board Connections**

**DANGER**

**High Voltage Hazard**

ONLY QUALIFIED PERSONNEL SHOULD HANDLE THE CDB1601-120W.




**WARNING:**

Heatsinking is required for Q4.

The end product should use tar pitch or an equivalent compound for this purpose.  
For lab evaluation purposes, a fan is recommended to provide adequate cooling.

## 2. SCHEMATIC




**Figure 2. Schematic**

### 3. BILL OF MATERIALS


#### CIRRUS LOGIC CDB1601-120W\_Rev\_C BILL OF MATERIAL (Page 1 of 1)

Item	Cirrus PN	Rev	Description	Qty	Reference Designator	MFG P/N	Notes
1	070-00157-21	A	DIODE RECT BRIDGE 600V 4A NPb GBU	1	BR1	MICRO COMMERCIAL CO	
2	011-00042-21	A	CAP 2200pF ±10% 2000V CER NPb RAD	2	C1C2	MURATA	DEB332222KA2B
3	011-00056-21	A	CAP 0.022µF ±20% 305V PLY FILM NPb TH	0	C3	EPICOS	B3293C3224M
4	011-00064-21	A	CAP 0.47µF ±20% 305V PLY FILM NPb TH	0	C4	PANASONIC	EC0292C2347AM
5	013-00054-21	A	CAP 0.33µF ±10% 630V POLY NPb RAD	1	C5	NICHICON	ECD6334KF
6	012-00186-21	A	CAP 47uF ±20% 80V CER NPb RAD	2	C6 C14	KEMET	C1206C330UJGAC
7	001-00528-21	A	CAP 330pF ±5% 30V CER NPb 1206	1	C7	KEMET	C1206C331KSGAC
8	001-00578-21	A	CAP 330pF ±10% 30V CER NPb 1206	0	C8	TOK	C3210XTR1E475N
9	001-00233-21	A	CAP 47uF ±20% 25V XTR NPb 1206	1	C9	KEMET	C1206C101E475N
10	001-00554-21	A	CAP 100pF ±4% 50V CIG NPb 1206	1	C10	KEMET	C1206C222KGRAC
11	001-00276-21	A	CAP 2200pF ±10% 50V NPb 1206	0	C11 C12	EPICOS	B3291C2324M
12	011-00064-21	A	CAP 0.022µF ±20% 330V PLY FILM NPb TH	1	C13	DIODES INC	1NA00066-T
13	070-00132-21	A	DIODERECT 800V 1.20mA NPDO-41	1	D1	DIODES INC	MU56380T3G
14	070-00166-21	A	DIODERECT 800V 1A UL1571 NPb SMC	1	D2	DIODES INC	L4148
15	070-00001-21	A	DIODES 5V 500mW NPb SOD80	1	D4		
16	180-00022-21	A	FUSE 3.15A 110V IEC NPb SHORT TR5	1	F2	LITTLE FUSE	3721310411
17	311-00019-21	A	HTSNK/NV LOCK TAB 5° TO220NPb	1	H51	AAVID THERMALLOY	6021FBG
18	115-00014-21	A	HDR 2x1 MLL 1" 062BBD ST GLD NPb TH	2	J1 J3	SAMTEC	TSW-102-07-G-S
19	110-00301-21	A	CON POS TERM BLK 5.08mm SFR NPb RA	1	J7 J6	WEIDMULLER	1716030000
20	110-00302-21	A	CON POS TERM BLK 5.08mm SFR NPb RA	1	J7	WEIDMULLER	1716020000
21	080-00001-21	A	WIRE AWG 20 SOLID PVC INS BLK NPb	6,000	JH1P1-JMP2-JMP3-JMP4 W2	ALPHA WIRE COMPANY	30501/BK005
22	050-00039-21	A	XENR 5mH 1.1150uH/ms 4PN NPb TH	1	L1	Premier Magnetics	TSU-2796
23	050-00060-21	A	XENR 300uH 10% 2656uH TH	1	L2	RENO	RGS-1005
24	040-00172-21	A	IND 1mh 1.3A ±15% FOR VERT NPb TH	1	L3	BOURNS	2724-V-RC
25	040-00172-21	A	IND 1mh 1.3A ±15% FOR VERT NPb TH	0	L4	BOURNS	NO POP
26	050-00039-21	A	XENR 5mH 1.1150uH/ms 4PN NPb TH	0	L5	Premier Magnetics	TSU-2796
27	050-00047-21	A	XENR COMMON MODE CHOKES 3.4TH NPb	0	L6 L7	RENO	RL4400-2-4.00
28	304-00042-21	A	SPCR STANDOFF 4-40-THR .500L NPb	4	MHH MH3 MH4	KEYSTONE	2203
29	071-00107-21	A	TRAN MOSFET nCh 1.1A 600V NPb T0220FP	1	Q4	ST MICRO ELECTRONICS	STT-1N4NN0N
30	020-00337-21	A	RES 0.1OHM 1A/W ±1% NPb 1206 FILM	1	R1	CRCW120624RKEA	CRCW1206100FKEA
31	020-00261-21	A	RES 100 OHM 1A/W ±1% NPb 1206 FILM	0	R2	CRCW1206100FKEA	NO POP
32	020-00273-21	A	RES 0 OHM 1A/W ±1% NPb 1206 FILM	2	R3 R6	CRCW1206000ZDEA	CRCW1206100FKEA
33	020-00273-21	A	RES 17K OHM 1A/W ±1% NPb 1206 FILM	1	R5	CRCW120624RKEA	NO POP
34	020-00390-21	A	RES 20K OHM 1A/W ±1% NPb 1206 FILM	1	R6	DALE	C603R1000F/280
35	020-00310-21	A	RES 0.1OHM 2W ±1% WWW NPb AXL	0	R8	VISHAY	NO POP
36	030-00091-21	A	RES 0.1OHM 2W ±1% WWW NPb AXL	1	R9	VISHAY	NO POP
37	030-00091-21	A	RES 1.1MHM 1.1A/W ±1% NPb 206	6	R10 R11 R12 R13 R15 R16	DALE	CRCW12061M15FKEA
38	020-00366-21	A	RES 1K OHM 1A/W ±1% NPb 1206 FILM	1	R14	CRCW12061K0FKEA	NO POP
39	020-00261-21	A	RES 17K OHM 1A/W ±1% NPb 1206 FILM	1	R17	DALE	ERJ11TRQFR24U
40	020-00391-21	A	RES 0.2A OHM 1W ±1% NPb 2512	0	R18 R22	PANASONIC	294-100K-RC
41	020-00372-21	A	RES 100K W ±5% MTL FILM NPb AXL	2	R19 R20	XICON	EPICOS
42	030-00080-21	A	VARISTOR 470V RMS 4A/M NPb RAD	0	RV1	KEYSTONE	S41K300
43	036-00015-21	A	CON TEST PT. CTR IN PLAT NPH BLK	7	T12 TP3 TP4 TP5 TP7 TP8	CIRRUSS LOGIC	5001
44	110-00045-21	A	IC CRUS LPWR FACTOR CORR NPH SOTC8	1	U1	CIRRUSS LOGIC	CS1601-FS72A2
45	065-00033-21	A	WIRE 281 AWG. KYNAR MOD. 500FT	2,000	W1	SQUIRES	L500 UL1422 281 BLU
46	080-00002-01	A	WIRE 16AWG SOLID PVC INS BLK NPb	4,000	W3	ALPHA WIRE COMPANY	305771/BK005
47	080-00040-21	A	HTSNK CO220 MOUNTING KIT NPb	1	X1S1	AAVID THERMALLOY	48890G
48	311-00025-21	A	SCREW 4-40X16 PH/MACH SS NPb	4	XMH1MMXHP2 XMH4	BUILDING FASTENERS	FMS55 440-0031 PH
49	300-00025-21	A	PCB CDB1601-120W-Z-NPb	1	Y1	CIRRUSS LOGIC	240-00466-21
50	240-00466-21	C	ASSY DVG CDB1601-120W-Z-NPb	REF	Z1	CIRRUSS LOGIC	600-00466-21
51	600-00466-21	C	SCHEM CDB1601-120W-Z-NPb	REF	Z1	CIRRUSS LOGIC	ECO865/S20/8640
52	600-00466-21	C	LBL SUBASSY PRODUCT ID AND REV	1	Z1	CIRRUSS LOGIC	422-00013-01


#### 4. BOARD LAYOUT



**Figure 3. Solder Mask (Bottom)**



**Figure 4. Solder Mask (Top)**



**Figure 5. Silkscreen (Top)**




Figure 6. Circuit Routing (Bottom)



Figure 7. Solder Paste Mask (Bottom)






Figure 8. Silkscreen (Bottom)


## 5. TYPICAL PERFORMANCE PLOTS




**Figure 9. Efficiency vs. Output Power**




**Figure 10. Power Factor vs. Output Power**




**Figure 11. THD vs. Output Power**




**Figure 12. V<sub>Link</sub> Voltage vs. Output Power**





**Figure 13. Steady State Waveforms — 120 VAC**






**Figure 14. Steady State Waveforms — 230 VAC**




**Figure 15. Steady State Waveforms — 277 VAC**









**Figure 20. Switching Frequency Profile at Peak of AC Line Voltage — 230 VAC**




**Figure 21. Switching Frequency Profile at Peak of AC Line Voltage — 230 VAC (cont.)**




**Figure 22. Switching Frequency Profile at Trough of AC Line Voltage — 230 VAC**





**Figure 23. Switching Frequency Profile at Trough of AC Line Voltage — 230 VAC (cont.)**




**Figure 24. Switching Frequency Profile at Peak of AC Line Voltage — 277 VAC**




**Figure 25. Switching Frequency Profile at Peak of AC Line Voltage — 277 VAC (cont.)**







**Figure 28. Transient — 15W to 115W Load at 10W/μs, Vin = 120VAC**




**Figure 29. Transient — 15W to 115W Load at 10W/μs, Vin = 120VAC (cont.)**




**Figure 30. Transient — 15W to 115W Load at 10W/μs, Vin = 230VAC**




**Figure 31. Transient — 15W to 115W Load at 10W/μs, Vin = 230VAC (cont.)**




**Figure 32. Transient — 15W to 115W Load at 10W/μs, Vin = 277VAC**





**Figure 33. Transient — 15W to 115W Load at 10W/μs, Vin = 277VAC (cont.)**




**Figure 34. Transient — 115W to Zero Load at 10W/µs, Vin = 120VAC**




**Figure 35. Transient — 115W to Zero Load at 10W/µs, Vin = 120VAC (cont.)**





**Figure 38. Transient — 115W to Zero Load at 10W/μs, Vin = 277VAC**



**Figure 39. Transient — 115W to Zero Load at 10W/μs, Vin = 277VAC (cont.)**

## 6. REVISION HISTORY

Revision	Date	Changes
DB1	FEB 2011	Initial Release.
DB2	FEB 2011	Minor BOM change.
DB3	MAR 2011	Updated BOM & Layers to rev C.