

115-41500

Article Number: 115-41500

Description: Releasable Cable Tie, Release Tab, 34.7" Long, 250lb Tensile Strength, PA66, Black, 25/pkg



Base Data	Local Order Number	RT250L0X2
	Type	RT250L
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Special extended-pawl design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>• Buckle feature on head allows excess strap to be tucked away after installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Releasable Cable Tie, Release Tab, 34.7" Long, 250lb Tensile Strength, PA66, Black, 25/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		1115.0N
Length L (Imperial)		34.7"
Length L (Metric)		880.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		Yes
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.49"
Width W (Metric)		12.5mm
Cable Tie Width Max. (Imperial)		0.49"
Cable Tie Width Max. (Metric)		12.5mm

115-41500



Product Dimensions	Bundle Diameter Min. (Imperial)	0.47"
	Bundle Diameter Min. (Metric)	12.0mm
	Bundle Diameter Max. (Imperial)	10.0"
	Bundle Diameter Max. (Metric)	254.0mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Minimum Application Temperature	-
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987