

170-03091



Article Number: 170-03091

Description: Braided Sleeve, Expandable, Flame Retardant, .5" Dia, PET, Black, 500 ft/bulk reel

Base Data	Local Order Number	170-03091
	Type	BSPFR120B
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.</li> <li>• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.</li> </ul>
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeve, Expandable, Flame Retardant, .5" Dia, PET, Black, 500 ft/bulk reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		152.4m
Reel Length (imperial)		500.0ft
Bundle Diameter Min. (Imperial)		0.25"
Bundle Diameter Min. (Metric)		6.4mm
Bundle Diameter Max. (Imperial)		0.75"
Bundle Diameter Max. (Metric)		19.1mm
Nominal Diameter (Imperial)		1/2"
Nominal Diameter (Metric)		12.7mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	VW-1

170-03091



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500ft
	Package Quantity (Metric)	152.4m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	3.6lbs
	Weight (Metric)	1.6kg