

Article Number: 596-00613

Description: Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll

**CAUTION: SOLAR ELECTRIC SYSTEM CONNECTED**

Base Data	
Local Order Number	596-00613
Type	CSESC
Color	Yellow (YE)
Features and benefits	<ul style="list-style-type: none"> <li>• Made with UV stable inks and materials for durability and weather resistance</li> <li>• Supplied with aggressive adhesive to ensure long life</li> <li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections</li> <li>• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers</li> </ul>
Quantity Per	roll
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	Pre-Printed Solar Label, Reflective, "SOLAR ELECTRIC SYSTEM CONNECTED", 6.5" X 1.0", Yellow
Local Order Number 2	Cross Reference = 10 per pack: 596-00672; Spanish version 50 per roll: 596-00821
Short Description	Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll
Product Dimensions	
Length L (Imperial)	6.5"
Length L (Metric)	165.1mm
Width W (Imperial)	6.5"
Width W (Metric)	165.1mm
Height H (Imperial)	1.0"
Height H (Metric)	25.4mm

596-00613



Material and Specifications		
	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	ANSI Standard Z535.4
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060
	Labels per Column	1
	Labels per Row	1