

## 57883-5000 1.0 I/O 50P 整線治具 仕様書

57883-5000 1.0 I/O 50P WIRING TOOL PRODUCT SPECIFICATION

ATP-57883-5000JE 2005/04/20, Rev.- C 日本モレックス株式会社 Molex Japan Co., Ltd.

## 1. 概要 / Description

.. ...

本治具は、モレックス社の1.0mmピッチ I/O 50P I/Oケーブルアッセンブリの圧接の前作業として、I/Oケー ブルの電線をアッパーカバーに整線するのに用いられる手動整線治具です。 特長としては、手動で電線ガイド櫛歯に布線した電線をアッパーカバーに一括押し込みし、その余長電線 をアッパーカバー端で切断します。 This tool is a manual-wiring tool that is used to arrange the wire of I/O cable into the upper cover as the pre-work of the termination of 1.0mm pitch I/O 50P cable assembly of Molex.

The arranged wire in the wire guide comb by the hand are pushed in a lamp into the upper cover as the feature and the excess wires are cut on the upper cover edge.

2.仕様	/ Specifications	
1) 治具	名称	1.0 I/O 50P 整線治具
Mac	hine name:	1.0 I/O 50P Wiring Tool
2) 治具		57883 - 5000
	hine number:	
3) 適合	コネクタ:	モレックス社 1.0mmピッチ I/O 50極コネクタ
Арр	licable connector:	52660-5011:50極プラグASS'Yキット
		Molex 1.0mm pitch I/O 50P connector
		52660-5011: 50P Plug assembly kit
4) 適合	ケーブル:	UL20276, #28 AWG 多芯編組シールドケーブル、被覆外径= 0.50~
App	licable cable:	0.58mm、ケーブル外径 = 7.0mm以下
		UL20276, #28 AWG Multi-pair braid shield cable, Insulation outer
		diameter = phi0.50- phi0.58mm, Cable outer diameter = 7.0mm or
		less
5) 布線	方式:	手で治具の櫛歯に電線を配置し、治具ハンドルを押し下げて電線をアッパ
Wire	e arrangement	ーカバーに一括押し込みします。
met	nod:	The wire is arranged in the comb of the tool by the hand, and the
		wires are pushed in a lamp into the upper cover by depressing the
		tool handle.
6) 外形	寸法と重量:	180(横幅)x 380(深さ)x 440(高さ)mm、約16kgf
Out	er dimensions and	180(width)x 380(depth)x 440(height)mm, Approx. 16kgf
wei	ght:	

## 3. 治具外観 / Tool Appearance



