PHYSICAL INFRASTRUCTURE SYSTEMS

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

Wireless

Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Managemen Accessories

> Q. Index

LC Fiber Optic Connectors – Field Polish Termination

- TIA/EIA-604 FOCIS-10 compatible connectors
- Exceed TIA/EIA-568-B.3 requirements
- Connector housing and boot colors follow TIA/EIA-568-C.3 suggested color identification scheme
- Insertion loss: 0.10dB average (multimode and singlemode)
- Return loss: >20dB (multimode), >40dB (singlemode)
- Non-optical disconnect maintains data transmission under tensile loads for jacketed cable
- Each simplex connector includes connector body/ferrule assembly, crimp sleeve, one boot for 900µm buffered fiber and one boot for 1.6mm – 2.0mm jacketed cable and one dust cap; 3.0mm jacketed cable connectors are also available separately
- Each duplex connector includes two connector body/ferrule assemblies, two crimp sleeves, two boots for 1.6mm – 2.0mm or 3.0mm jacketed cable or two boots for 900µm buffered fiber, two dust caps and one duplex clip

- LC duplex clip available separately for duplexing two simplex Panduit LC Connectors
- Fiber cable type: tight-buffered recommended
- Fiber cable size: accept 1.6mm 2.0mm or 3.0mm jacketed cable, or 900µm buffered fiber (noted in part description)
- For 250µm coated fiber termination, use 250 micron fiber build-up tube kit or fan-out kits on pages C.27 – C.28
- Ferrule type: 1.25mm zirconia ceramic (highest durability for repeated matings)
- Field polish termination Panduit recommends anaerobic adhesive on pages C.103, C.104
- Use field polish termination kit (FIELDKIT) on pages C.103, C.104







FLCDMBLY

FLCDM3.0EI

Part Number	Part Description	Color	Std. Pkg. Qty.	Std. Ctn. Qty.
LC OM4/OM3/C	DM2 Multimode Fiber Optic Connectors			,
FLCSMBLY	LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation.	Black	1	10
FLCSM3.0BL	LC multimode simplex fiber optic connector for 3.0mm jacketed cable installation.	Black	1	10
FLCDMBLY	LC multimode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation.	Black	1	10
FLCDM900BLY	LC multimode duplex fiber optic connector for 900μm buffered fiber installation.	Black	1	10
FLCDM3.0BL	LC multimode duplex fiber optic connector for 3.0mm jacketed cable installation.	Black	1	10
LC OM1 Multim	node Fiber Optic Connectors			
FLCSMEIY	LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900um buffered fiber installation.	Electric Ivory	1	10

node Fiber Optic Connectors			
LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation.	Electric Ivory	1	10
LC multimode simplex fiber optic connector for 3.0mm jacketed cable installation.	Electric Ivory	1	10
LC multimode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation.	Electric Ivory	1	10
LC multimode duplex fiber optic connector for 900µm buffered fiber installation.	Electric Ivory	1	10
LC multimode duplex fiber optic connector for 3.0mm jacketed cable installation.	Electric Ivory	1	10
	LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation. LC multimode simplex fiber optic connector for 3.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 900µm buffered fiber installation. LC multimode duplex fiber optic connector for 3.0mm	LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation. LC multimode simplex fiber optic connector for 3.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 900µm buffered fiber installation. LC multimode duplex fiber optic connector for 900µm buffered fiber installation. LC multimode duplex fiber optic connector for 3.0mm Electric	LC multimode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation. LC multimode simplex fiber optic connector for 3.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation. LC multimode duplex fiber optic connector for 900µm buffered fiber installation. LC multimode duplex fiber optic connector for 900µm buffered fiber installation. LC multimode duplex fiber optic connector for 3.0mm Electric 1

Q. Index

LC Fiber Optic Connectors – Field Polish Termination (continued)





FLCCLIP-L

Part Number	Part Description	Color	Std. Pkg. Qty.	Std. Ctn. Qty.
LC OS1/OS2 Si	nglemode Fiber Optic Connectors			
FLCSSBUY	LC singlemode simplex fiber optic connector for 1.6mm – 2.0mm jacketed cable or 900µm buffered fiber installation.	Blue	1	10
FLCSS3.0BU	LC singlemode simplex fiber optic connector for 3.0mm jacketed cable installation.	Blue	1	10
FLCDSBUY	LC singlemode duplex fiber optic connector for 1.6mm – 2.0mm jacketed cable installation.	Blue	1	10
FLCDS900BUY	LC singlemode duplex fiber optic connector for 900µm buffered fiber installation.	Blue	1	10
FLCDS3.0BU	LC singlemode duplex fiber optic connector for 3.0mm jacketed cable installation.	Blue	1	10
LC 10Gig™ OM:	3/OM4 Field Polish Boots			
FLCBT900AQ-X	LC 10Gig [™] OM3/OM4 Field Polish Boot for 900μm buffered fiber.	Aqua	10	100
FLCBT2AQ-X	LC 10Gig [™] OM3/OM4 Field Polish Boot for 1.6/2.0mm jacketed cable.	Aqua	10	100
FLCBT3AQ-X	LC 10Gig [™] OM3/OM4 Field Polish Boot for 3.0mm jacketed cable.	Aqua	10	100
LC Duplex Clip				
FLCCLIP-L	LC duplex clip for duplexing two simplex Panduit LC field polish multimode or singlemode connectors.	White	50	_