

Model #: P450-006

6-ft. Null Modem Gold Cable (DB9 F/F)



Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6ft cable has a DB9 female connector on each end. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

System Requirements

• Two serial devices with DB9M connectors requiring a null modem (cross-wired) configuration

Package Includes

• 6-ft. Null Modem Gold Cable DB9F to DB9F

Features

- DB9 female to DB9 female
- Full Handshake Null wiring configuration: 1+6 4, 2-3, 3-2, 4 1+6, 5-5, 7-8, 8-7.
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW		
Intended Application	Connecting Peripherals	
Cable Type	NULL MODEM	
INPUT		
Cable Length (ft.)	6	
Cable Length (m)	1.83	
UPC Codes		

Unit Carton UPC#	037332013323			
PHYSICAL				
Color	Black			
Style	Null Modem Cables			
CONNECTIONS				
Connector A	DB9 (FEMALE)			
Connector B	DB9 (FEMALE)			
WARRANTY				
Product Warranty Period (Worldwide)	Lifetime limited warranty			

Related Items

Optional Products

Related Model	Description	Qty.
P404-006	6-ft. AT Serial Modem Gold Cable (DB25M to DB9F)	1
P454-006	6-ft. Null Modem Gold Cable (DB9 F/M)	1
P456-006	6-ft. Null Modem Gold Cable (DB9F to DB25M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2259.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.