



SML-11 Series

3020(1208) 3.0×2.0mm(t=1.6mm)

Features

- ·Side-view with reflector type
- •3.0×2.0mm t=1.6mm












Specifications


	1																		
				Abso	lute Maxim	um Rating	s (Ta=25℃)		Electrical and Optical Characteristics (Ta=25°C)										
Part No.	Chip	Emitting	Power		Peak Forward		Operating								veleng				
r divivo.	Structure	Color	Dissipation PD(mW)	Current IF(mA)	Current IFP(mA)	Voltage VR(V)	Temperature Topr(°C)	Temperature Tstg(°C)	Typ.(V)	lF(mA)	Max. (μA)	VR(V)	Min.*2 (nm)	Typ. (nm)	Max.* ² (nm)	IF(mA)	Min. (mcd)	n. Typ. Iranschip (mcd) Iransc	IF(mA)
■SML-110VT		Red							2.0				625	630	635		2.2	6.3	
SML-110DT	GaAsP on GaP	Orange							2.0				602	605	608		3.6	10	
SML-110YT		Yellow		25	60*1	4	-30 to +85	-40 to +85	2.1	20	100	4	587	590	593	20	2.2	6.3	20
SML-110MT		Yellowish Green	70	25	60	4	-30 10 +65	-40 10 +65		20	100	-	569	572	575	20	5.6	16] 20
■ SML-110FT	GaP	Green							2.2				562	565	568		3.6	10	
SML-110PT		Green											557	560	563		2.2	6.3	


*1:Duty1/5, 200Hz / *2:Reference

Dimensions




Recommended Solder Pattern Viewing Angle






Electrical Characteristics Curves


Forward Current-Forward Voltage




Luminous Intensity-Atmosphere Temperature



Luminous Intensity-Forward Current



Derating



Rank Reference of Brightness

Red (V)

											(Ta=25°C,	$I_F=20mA$
Г		Package	Luminous	G	Н	J	K	L	M	N	P	Q
		size(mm)		1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63
	Side View (reflector)	3020	1.6				SML-	110VT				

Orange (D)

											(Ta=25°C,	$I_F=20mA$
	p	Package	Luminous	G	Н	J	K	L	M	N	Р	Q
		ciza(mm)		1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63
Side V (reflec		3020	1.6					SML-				


Yellow (Y)

										(Ta=25°C,	IF=20mA)
	Package	Luminous Intensity	G	Н	J	K	L	М	N	P	Q
	cize(mm)		1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63
Side View (reflector)	3020	1.6				SML-	110YT				

Green (M, P, F)

											1a=25 C,	IF-ZUITIA
	Package	Luminous	F	G	Н	J	K	L	M	N	Р	Q
	size(mm)		0.63 to 1.0	1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63
									SML-1	110MT		
Side View (reflector)	3020	1.6						SML-	110FT			
(SML-	110PT				

Part No. Construction



- * Concerning the Brightness rank
- Please refer to the rank chart above for luminous intensity classification.
 Part name is individual for each rank.
- When shipped as sample, the part name will be a representative part name. General products are free of ranks. Please contact sales if rank appointment is needed.

Packing Specification

ROHM LED products are being shipped with desiccant (silica gel) concluded in moisture-proof bags.

Please contact the nearest sales office or distributer if necessary.

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/