

151-06501



Article Number: 151-06501

Description: Dual Swivel Saddle Spacer for T50-T250, .63"-6" Bundle Diameter, Black, POM, PA66HS, 500/pkg

Base Data	Local Order Number	DSWS50HSH1
	Type	DSWS5
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • "H" profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle. • Swivels in 360 degree motion to accommodate any area. • Accommodates T50-T250 ties to handle both light duty and heavy duty applications.
	Quantity Per	bag
	Product Description	These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The mounts can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the mounts. The dual swivel saddle spacers accommodate cable ties up to 1/2" wide
	Short Description	Dual Swivel Saddle Spacer for T50-T250, .63"-6" Bundle Diameter, Black, POM, PA66HS, 500/pkg
	Product Dimensions	Length L (Imperial)
Length L (Metric)		40.6mm
Fixation Method		None
Width W (Imperial)		1.0"
Width W (Metric)		25.4mm
Height H (Imperial)		0.9"
Height H (Metric)		23.6mm
Bundle Diameter Min. (Imperial)		0.7"
Bundle Diameter Min. (Metric)		16.0mm
Bundle Diameter Max. (Imperial)		6.0"
Bundle Diameter Max. (Metric)		152.0mm

151-06501



Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Minimum Extraction Force (Imperial)	250.0lbs
	Minimum Extraction Force (Metric)	1112N
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987