# **SSF50 Series**



## Compact Float Switch with Integral Slosh Guard & Optional Check Facility



The SSF50 series is a compact vertical float switch with an integral acrylic slosh guard to reduce inadvertent operation in turbulent fluids. The unit can be mounted to a vertical surface or via a U-bolt (not supplied) using the integrated mounting bracket.

The metal components are manufactured from a combination of 316 and 304 grade stainless steels.

The switch action may be reversed by removing the float, inverting and then refitting it to the central stem.

The unit can be supplied complete with an integral test facility whereby the float can be manually raised to check the operation of the switch.

Cynergy3 Components Ltd. 7 Cobham Road Ferndown Industrial Estate Wimborne, Dorset BH21 7PE *Telephone +44 (0) 1202 897969 Email:sales@cynergy3.com* 

IS09001 CERTIFIED

SSF50 2016

- Bracket mounted
- Stainless steel 316 & 304
- Compact design

- Temperature up to 80°C
- With or without check facility
- User configurable N/O (make on rise) or N/C (make on fall)

Mounting style	Mounting bracket included	Cable length - standard	100cm
Cable size	17/0.16 - AWG22	Cable Entry Rating	IP67
Float & Stem material	316 and 304 grade SS	SLOSH shield material Acrylic 60mm dia x 4mm	
Cable sheath material	FEP	Total Weight (-C version)	335g
Maximum pressure	20 bar	Maximum Temperature 80°C	U U
Float SG	0.7	Minimum fluid SG	0.8

Electrical Specification		
Contact Form		N/O (N/C)
Switching Power Max	W (VA)	50 (70)
Switching Voltage AC Max	V	240
Switching Voltage DC Max	V	200
Switching Current Max	A	0.5
All ratings are for resistive	load only.	

Standard Parts	Description
SSF50X100X	Without check facility
SSF50X100X-C	With check facility

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

www.cynergy3.com

© 2016 Cynergy3 Components, All Rights Reserved. Specifications are subject to change without prior notice. Cynergy3 Components and the Cynergy3 Components logo are trademarks of Cynergy3 Components Limited.

# **SSF50 Series**



58±

## Compact Float Switch with Integral Slosh Guard & Optional Check Facility

Mechanical Dimensions  $28 \pm 1$ SSF50X100X-C ØЗ ØЗ L1 = 21.5158± 1 I.1 = 21.5Ĉ 14 <u><u></u></u> 120 120 22 108.9 22 108.9 == Ø 38 Ø 38 L0=91L0=91 Ø <u>60</u> Ø 60 0 0 +62 10 5 12 Ø 9.5 Ø 9.5 Ø 20 Ø 20  $20 \pm 1$ 48.5± SSF50X100X L1=21.5 1=21.5Ĉ Ĉ 14 14 LC L 5 120 52 120 52 108.9 108.9 Ø 38 Ø 38 L0=91 L0=91 Ø60 Ø 60 0 0 \_\_\_\_ 17 Þ Cynergy3 Components Ltd. Ø 9.5 7 Cobham Road Ø 9.5 Ferndown Industrial Estate Wimborne, Dorset BH21 7PE Ø20 Ø20 Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

### IS09001 CERTIFIED

#### www.cynergy3.com

© 2016 Cynergy3 Components, All Rights Reserved. Specifications are subject to change without prior notice. Cynergy3 Components and the Cynergy3 Components logo are trademarks of Cynergy3 Components Limited.