Q

Print

Share

Search Keywords, part numbers, etc

Need Help?

Contact Us

Ouestions? We can help



3M[™] Particulate Respirator 8511, N95 80/Case

3M ID 70070757557 UPC# 50051138543438 3M Product Number 8511 CAT# 8511





This disposable N95 particulate respirator features the proprietary 3M[™] Cool Flow[™] Valve and helps provide comfortable, reliable worker respiratory protection. It is ideally suited for hot/dusty work settings that require long periods of wear.

- NIOSH approved for at least 95 percent filtration efficiency against certain non-oil based particles
- 3M Cool Flow Exhalation Valve reduces heat build-up inside the respirator
- Adjustable M-noseclip reduces potential for eyewear fogging
- Braided headbands two-strap design with dual point attachment helps provide a secure seal
- 3M Cool Flow Exhalation Valve reduces heat build-up inside the respirator
- Spacious and durable
- Designed to increase comfort and wearability
- Advanced Electret Media is designed for ease of breathing

Like Sign Up to see what your friends like.

verview Documents

3M[™] Particulate Respirator 8511, N95 is a disposable particulate respirator that is designed to help provide reliable respiratory protection of at least 95 percent filtration efficiency against certain non-oil based particles. The respirator is designed for use for particles such as those from grinding, sanding, sweeping, sawing, bagging, or other dusty operations. This respirator can also help reduce inhalation exposures to certain airborne biological particles (examples: mold, Bacillus anthracis, Mycobacterium tuberculosis), but cannot eliminate the risk of contracting infection, illness, or disease. Soft inner material provides added comfort while the cup shape design makes the respirator incorporates 3M's proprietary technology with advanced electrostatically charged microfiber filter media designed for ease of breathing. This respirator is compatible with a variety of protective eyewear and hearing protection.

Fitted with a 3M Cool Flow™ Exhalation Valve, this respirator is ideally suited for work situations involving heat, humidity, or long periods of wear. The proprietary 3M Cool Flow valve is designed to release hot, humid exhaled breath quickly, helping to prevent an unpleasant build up of heat inside the facepiece - a significant cause of discomfort to respirator wearers. The Cool Flow valve's efficiency in keeping breathing cool and comfortable has been demonstrated through testing*: the atmosphere inside a respirator with a Cool Flow valve is on average 7.5°F cooler than the similar product without the valve. This makes Cool Flow valve respirators ideal for long periods of wear, especially where conditions are hot, humid or physically demanding. *Testing conducted in a 3M laboratory. Testing protocol, data generation and conclusions were reviewed and approved by an expert from The University of Minnesota. The testing performed by 3M is not a part of the testing and certification conducted by NIOSH.

This particulate respirator is NIOSH (National Institute for Occupational Safety and Health) approved for environments containing certain non-oil based particles and provides at least 95 percent filter efficiency.

Breathing hazardous particles can pose a risk to your health. NIOSH, a Federal government regulatory agency, has tested and approved the 3M Particulate Respirator 8511, which is designed to help reduce exposure to certain airborne particles. WARNING: These respirators help reduce exposures to certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. In the U.S., a written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For proper use, see package instructions, supervisor, or call 3M OH&ESD Technical Service in USA at 1-800-243-4630 and in Canada at 1 -800-267-4414.

Aerosol Type	Non-Oil
Color	White
Exhalation Valve	Yes
FDA Cleared	No
Features	Braided Comfort Strap, M Noseclip, Stapled Headband
Flame Resistance (ASTM D2859-96)	No
luid Resistant (ASTM 1862)	N/A
National Stock Number	4240-01-247-2348
latural Rubber Latex Components	No
Product Type	Dust and other Particles
ecommended pplication	Agricultural Production, Airborne Biological Particles, Assembly and Mechanical, Bagging, Cleaning, Dry Chemical Handling, Foundry Operations, Grinding, Petrochemical, Pharmaceutical Manufacturing, Processing of Minerals, Sanding, Textile Operations
Recommended Industry	Construction, General Manufacturing, Mining, Oil & Gas, Transportation
Respirator Style	Cup
Size	Standard
Standards/Approvals	KMOEL P1, N95
IS Govt Contract lumber	GS-07F-0374J

3M Defense: <u>Products</u> <u>Capabilities</u> <u>About 3M Defense</u> <u>Support</u> <u>Contact Us</u>

3M: News Careers Partners & Suppliers Investor Relations MSDS Search Transport Information Search Contact 3M

Legal Information Privacy Policy

© 3M 2014. All Rights Reserved.

