

560-10228

HellermannTyton

Article Number: 560-10228

Description: Clip-Tag marked 2, .075"-.104", Nylon, White, 300/pkg



| | | |
|-----------------------------|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base Data | | |
| | Local Order Number | WC3-2 |
| | Type | WC3 |
| | Color | White (WH) |
| | Features and Benefits | <ul style="list-style-type: none"> • Clip-Tags are snap-on markers which slip easily on wire and cable. • Markers are non-adhesive and come on a plastic wand for trouble free installation. • Interlocking design of these markers help to keep them aligned and readable. • Clip-Tags have an opening on one end which means that they can be used on pre-terminated and pre-installed wires attached to terminal blocks. |
| | Quantity Per | pack |
| | Product Description | ClipTags are "open" markers that has an open end which can be snapped over pre-terminated cables. Each legend is printed black on white and has a very low profile when applied to wire and cable. Available in printed legends 0 to 9, + and -, each package contains 300 pieces. |
| | Technical Description | Clip-Tag marked 2, .075"-104", White |
| | Short Description | Clip-Tag marked 2, .075"-.104", Nylon, White, 300/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 0.125" |
| | Length L (Metric) | 3.19mm |
| | Outside Diameter Min. (Imperial) | 0.075" |
| | Outside Diameter Min. (Metric) | 1.9mm |
| | Outside Diameter Max. (Imperial) | 0.104" |
| | Outside Diameter Max. (Metric) | 2.65mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |

560-10228



| | | |
|------------------------|-----------------------------|------------|
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 300 |
| | Package Quantity (Metric) | 300 |
| | Customs Number(Schedule B) | 3926909987 |