

151-07300



Article Number: 151-07300

Description: Heavy-Duty Mount, .38" Mounting Hole, 40lb-ft Max Torque, PA66HIRHSUV, Black, 500/pkg

Base Data	Local Order Number	HDM401HIHSUVH4
	Type	HDM401
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Mount and tie combination makes it easy to service bundles in the field.</li> <li>• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.</li> <li>• Eliminates the needs for multiple sized fix diameter clamps.</li> </ul>
	Quantity Per	bag
	Product Description	This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.
	Short Description	Heavy-Duty Mount, .38" Mounting Hole, 40lb-ft Max Torque, PA66HIRHSUV, Black, 500/pkg
Product Dimensions	Length L (Imperial)	1.8"
	Length L (Metric)	46.0mm
	Fixation Method	Screw Mounting and Rivet
	Width W (Imperial)	0.96"
	Width W (Metric)	24.0mm
	Cable Tie Width Max. (Imperial)	0.5"
	Cable Tie Width Max. (Metric)	12.7mm
	Height H (Imperial)	0.8"
	Height H (Metric)	20.7mm
	Mounting Hole Diameter D (Imperial)	0.375"
	Mounting Hole Diameter D (Metric)	9.5 mm
Material and Specifications	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

151-07300



Material and Specifications	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Maximum Torque (kgf-cm)	553kgf-cm
	Maximum Torque (lbf-ft)	40lbf-ft
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987