

## Shrink sleeve - WMS 6,4 (15X10)R - 0801593

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOMARK W, THERMOMARK ROLL, THERMOMARK X, THERMOMARK S1.1, Perforated, Lettering field: 15 x 10 mm



The illustration shows WMS 6,4 (30X10)R

### Product Features

- WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- The sleeves are pre-assembled for optimum use of material
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- The sleeves remain flexible after shrinking
- Up to four markers per sleeve are separated by perforations
- UL 224 (125°C, 600 V, all tubing)
- CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)

### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	1.0 GRM
Country of origin	China

### Technical data

#### Dimensions

Length (b)	15 mm
Width (a)	10 mm

#### General

Color	white
Base element material	polyolefine
Components	Halogen-free
Material	Polyolefine
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	250

## Shrink sleeve - WMS 6,4 (15X10)R - 0801593

### Classifications

#### eCl@ss

eCl@ss 4.1	24190219
eCl@ss 5.1	27141137
eCl@ss 6.0	27400401
eCl@ss 8.0	27400401

#### ETIM

ETIM 4.0	EC000217
ETIM 5.0	EC001530