

318-60155 Article Number:

Hallermann) but Hallermann, bu Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 3/4", 19.0/6.0 Dia, PO, Black, 15/pkg

Base Data		
	Local Order Number	318-60155
	Туре	TAN33-ST-19/6 BK
	Color	Black (BK)
	Features and Benefits	 Adhesive lining provides an excellent seal against moisture and humidity. 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters, while thin exterior wall is very flexible and provides superior insulation. Meets UL224 VW-1 specifications making it ideal high heat applications (excludes clear tubing). Polyolefin material provides mechanical strength with good resistance to solvents oils and fuels.
	Quantity Per	pack
	Product Description	TAN33 is a flexible, thin wall adhesive lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity. 4-foot sticks are individually labeled for retail.
	Short Description	Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 3/4", 19.0/6.0 Dia, PO, Black, 15/pkg
Product Dimensions		
	Length L (Imperial)	4.0ft
	Length L (Metric)	1.22m
	Printable (Yes/No)	No
	Shrink Ratio	3:1
	Trade Size	3/4 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 ¹⁴ Ω cm
	Nominal Diameter (Imperial)	3/4"
	Nominal Diameter (Metric)	19mm
	Wall Thickness WT (Imperial)	.085"

2.15mm

6.0mm

generated on: 4/28/2017

Wall Thickness WT (Metric)

Recovered Diameter d (metric)

318-60155



Recovered Diameter d (imperial)	0.236"
Supplied Diameter D (imperial)	0.748"
Supplied Diameter D (metric)	19.0mm
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Elongation at break	400%
Halogenfree	No
Shrink Temperature	+212 °F (+100 °C)
Operating Temperature	-67°F to +257°F (-55°C to +125°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	15
Package Quantity (Metric)	15
Customs Number(Schedule B)	3926909987
	Supplied Diameter D (imperial) Supplied Diameter D (metric) Material Material Shortcut Elongation at break Halogenfree Shrink Temperature Operating Temperature ROHS Compliant JL Recognized (US) Package Quantity (Imperial) Package Quantity (Metric)

generated on: 4/28/2017