


# 500mw Audio Miniature Epoxy Potted *108 Series*

PC Board Mount

## Features



- Perfect for audio input, line matching, isolation or output transformer applications.
- 500 milliwatt (+/- 1.5 db, 300 Hz. - 50 KHz.).
- Epoxy potted in an attractive black molded case, Pin type P.C. board mount (min. 0.187" length).
- In some models where no center tap is required (on secondary), pin No. 5 is omitted.
- Power level ratings are maximum at lowest frequency rating (see charts & PDF spec. sheets below)
- Power can be increased slightly at higher frequencies. See individual PDF specs. for specifics.
- Will withstand soldering for 10 sec. @ 260 degrees C, ambient temp. 85 degrees C max.

Part No.	Nominal Impedance (Ohms)		D.C. Resistance (Ohms) +/- 20%		Max. D.C. Unbalance (ma.)
	Primary (Pins 1-3)	Secondary (Pins 4-6)	Primary (Pins 1-3)	Secondary (Pins 4-6)	
<b>108E</b>	600 ct	3.2	65	0.43	6
<b>108F</b>	600 ct	150 ct	65	18	6
<b>108G</b>	600 ct	250 ct	65	29	6
<b>108H</b>	600 ct	600 ct	65	69	6
<b>108J</b>	1K ct	600 ct	109	69	4.5
<b>108K</b>	1.5K ct	600 ct	170	69	4
<b>108L</b>	10K ct	3.2	1050	0.43	1.5
<b>108N</b>	10K ct	600 ct	1050	69	1.5
<b>108P</b>	10K ct	1.5K ct	1050	180	1.5
<b>108T</b>	10K ct	10K ct	1050	1200	1.5

*Data subject to change without notice*