BGA Heat Sink - High Performance Ultra Low Profile





ATS Part#: ATS-60004-C1-R0

Description: 58.20 x 61.00 x 6.10 mm BGA Heat Sink - High Performance Ultra Low Profile

Heat Sink Type: Ultra Low profile
Heat Sink Attachment: Thermal Tape
Equivalent Part Number: ATS-60004-C2-R0

Features & Benefits

- bluelCE™ heat sinks feature an ultra low profile for tough-to-cool applications
- Designed for high performance in low air velocities
- · Ideal for telecommunications applications where space is limited
- · Comes preassembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.6 °C/W	3 °C/W	2.4 °C/W	2.3 °C/W	2 °C/W	1.9 °C/W	1.7 °C/W
	Ducted Flow	2.2	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	58.20 mm	61.00 mm	6.10 mm	67.8 mm	T412	BLACK-ANODIZED
	Dimension ATS-6000 (Saint-Go Thermal papplicatio ATS reserved performan ATS certification	rves the right to upd	neight from the botto ct heat sink assemb e provided for refere ate or change its pro	ly with an equivalence only. Actual pendeducts without notice	t thermal	interface material
*Image above is for illustration purpose only.						





^{*}Image above is for illustration purpose only.