

Capacitor, film, 0.68 uF, +/-20% Tol, -40/+110C, Safety: X1, 330VAC, Lead Spacing=22.5 mm



Dimensions (mm)

ID	Dimension	Tolerance
L	26.5	+0.3
H	22	+0.1
T	13	+0.2
S	22.5	+/-0.4
LL	4	+2
F	0.8	+/-0.05

Specifications

Manufacturer:	KEMET
Brand:	Arcotronics
Capacitance:	0.68 uF
Temperature Range:	-40/+110C
Rated Temperature:	110C
Voltage @ rated temp:	800V
Voltage AC:	330VAC
Tolerance:	+/-20%
Body Type:	Radial Box
Construction:	Wound
Application:	Safety: X1
Dissipation Factor @ 1 kHz:	0.1%
Insulation Resistance:	44.12 GOhm
Maximum dVdT:	400v/us
UL_1414:	250V
UL_1283:	310V
IEC_60384-14:	330V
C_22.2_NO.1:	250V
Package Kind:	Bulk
Package Type:	Bag
Package Quantity:	300



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.