

596-00009 Article Number:

Thermal Transfer Labels, Self-Laminating, .5" x .38" x .75" 5 Across, VL, White, 10,000/roll Description:

HellermannTyton

Base Data		
	Local Order Number	TAG26T6-100B
	Туре	TAG26T6
	Color	White (WH)
	Features and Benefits	 HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy. Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time. Labels are UL recognized for indoor and outdoor use to expand application options. HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.
	Quantity Per	reel
	Product Description	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
	Short Description	Thermal Transfer Labels, Self-Laminating, .5" x .38" x .75" 5 Across, VL, White, 10,000/roll
Product Dimensions		
	Length L (Imperial)	0.75"
	Length L (Metric)	19.05mm
	Width W (Imperial)	0.5"
	Width W (Metric)	12.7mm
	Height H (Imperial)	0.75"
	Height H (Metric)	19.05mm
	Height H2 (Imperial)	0.75"
	Height H2 (Metric)	19.1mm
	Height of printable area (imperial)	.375"
	Height of printable area (metric)	9.52mm
	Bundle Diameter Min. (Imperial)	0.059"

generated on: 4/28/2017

596-00009



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	0.118"
	Bundle Diameter Max. (Metric)	3.0mm
	Horizontal Repeat HR (metric)	12.7mm
	Horizontal Repeat HR (imperial)	0.50"
	Print Method	Thermal transfer
	Thickness T (Metric)	25µm
	Vertical Repeat VR (imperial)	1.0"
	Vertical Repeat VR (metric)	25.4mm
	Width of Liner WL (imperial)	3.35"
	Width of Liner WL (metric)	85.09mm
Material and Specifications		
	Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
	Material Shortcut	100B
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
Logistic and Packaging		
	Package Quantity (Imperial)	10000
	Package Quantity (Metric)	10000
	Customs Number(Schedule B)	3919102055
	Labels per Row	6
	Weight (Metric)	0.056kg

generated on: 4/28/2017