

111-03325

HellermannTyton



Article Number: 111-03325

Description: Standard Cable Tie, 7.8" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg

Base Data		
	Local Order Number	T30L9C2
	Type	T30L
	Color	Natural (NA)
	Features and benefits	• Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Standard Cable Tie, 7.8" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	30.0lbs
	Minimum Tensile Strength (Metric)	135.0N
	Length L (Imperial)	7.48"
	Length L (Metric)	198.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.14"
	Width W (Metric)	3.6mm
	Bundle Diameter Min. (Imperial)	0.059"
	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.97"

111-03325



Product Dimensions	Bundle Diameter Max. (Metric)	50.0mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	DNV GL IEC 62275:2006
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987