

170-03066

Article Number: 170-03066

Description: Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel



Base Data	Local Order Number	170-03066
	Type	BSPFR1128
	Color	Gray (GY)
	Features and Benefits	<ul style="list-style-type: none"> • Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. • Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		12.2m
Reel Length (imperial)		40.0ft
Bundle Diameter Min. (Imperial)		1.0"
Bundle Diameter Min. (Metric)		25.4mm
Bundle Diameter Max. (Imperial)		2.125"
Bundle Diameter Max. (Metric)		53.9mm
Nominal Diameter (Imperial)		1-1/2"
Nominal Diameter (Metric)		38.1mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	Mil-202

170-03066



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	40ft
	Package Quantity (Metric)	12.19m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.79lbs
	Weight (Metric)	0.358kg