

318-60158

Article Number: 318-60158

Description: Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1.5", 40.0/13.0 Dia, PO, Black, 6/pkg



Base Data	Local Order Number	318-60158
	Type	TAN33-ST-40/13 BK
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Adhesive lining provides an excellent seal against moisture and humidity.</li> <li>• 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters, while thin exterior wall is very flexible and provides superior insulation.</li> <li>• Meets UL224 VW-1 specifications making it ideal high heat applications (excludes clear tubing).</li> <li>• Polyolefin material provides mechanical strength with good resistance to solvents, oils and fuels.</li> </ul>
	Quantity Per	pack
	Product Description	TAN33 is a flexible, thin wall adhesive lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity. 4-foot sticks are individually labeled for retail.
	Short Description	Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1.5", 40.0/13.0 Dia, PO, Black, 6/pkg
	Product Dimensions	
	Length L (Imperial)	4.0ft
	Length L (Metric)	1.22m
	Printable (Yes/No)	No
	Shrink Ratio	3:1
	Trade Size	1-1/2 "
	Variant	Thin-Wall
	Volume Resistance (Ohm cm)	10 <sup>14</sup> Ω cm
	Nominal Diameter (Imperial)	1-1/2"
	Nominal Diameter (Metric)	40mm
	Wall Thickness WT (Imperial)	.094"
	Wall Thickness WT (Metric)	2.40mm
	Recovered Diameter d (metric)	13.0mm

318-60158



Product Dimensions	Recovered Diameter d (imperial)	0.512"
	Supplied Diameter D (imperial)	1.58"
	Supplied Diameter D (metric)	40.0mm
Material and Specifications		
	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	Elongation at break	400%
	Halogenfree	No
	Shrink Temperature	+212 °F (+100 °C)
	Operating Temperature	-67°F to +257°F (-55°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	6
	Package Quantity (Metric)	6
	Customs Number(Schedule B)	3926909987